

Speed Queen

COIN & CARD-OPERATED WASHER-EXTRACTORS NETMASTER™ CONTROL

20 lb (9 kg) WASHER-EXTRACTOR
25 lb (11 kg) WASHER-EXTRACTOR
30 lb (14 kg) WASHER-EXTRACTOR
40 lb (18 kg) WASHER-EXTRACTOR
60 lb (27 kg) WASHER-EXTRACTOR
80 lb (36 kg) WASHER-EXTRACTOR



Speed Queen®

BUILT BETTER TO LAST LONGER

LET SPEED QUEEN LEAD THE WAY...

As America's largest commercial laundry equipment manufacturer, Speed Queen stands for innovation. As a leader in laundry technology, our electronically controlled laundry units for coin and card operation will provide you with quality, efficiency, convenience, and flexibility well into the 21st century. Since 1908 we have been committed to our tradition of quality products, backed by superior customer service.

NetMaster™ System

Speed Queen's NetMaster™ System of technologically advanced laundry products offers more flexibility and accountability benefits than you ever thought possible. Now you can program vend prices, cycle times, rinse options, and cycle selections while auditing machine operation simply by touching a series of control pads.



There are three options available to program your machines—manual, Micro-Wand III™ and a network with NetMaster™ models. Whatever your needs, Speed Queen has the right option for you. It's almost like having a washer built to your specifications. Your customer will be amazed at how easy and convenient it is to launder garments.



Satisfied customers translate into profits for you.

CardMate Plus™ System

Speed Queen introduces a revolution in laundry room convenience, accountability and profitability.

The CardMate Plus™ System offers the industry's first commercial

washers and dryers with factory-installed, smart card reader controls on individual laundry units for cashless operation.



Both you and your customers will benefit from the convenience of CardMate Plus.™



WASHER-EXTRACTORS



Heavy Duty Construction

Durable 304 stainless steel cabinet front, sides and top, as well as inner and outer tubs, won't corrode, chip, crack or pit with normal use, and they're



extremely corrosion resistant. Our heavy-duty Gamma

A-Frame stands up to even the toughest laundry conditions, keeping Speed Queen washer-extractors durable for years to come.

Multi-Compartment Dispenser

Our self-cleaning, multi-compartment dispenser automatically dispenses detergent for prewash and main wash, and fabric softener for final rinse. Simple user instructions with clearly marked compartments make it easy for customers to use, promoting proper equipment usage.



Large Door Opening

Large door opening makes loading and unloading fast and easy. Our heavy-duty stainless steel door features vacuum tight sealing to keep water inside the machine where it belongs. The door lock, as well as the heat-treated, shatter-proof circular door glass, helps operators to safely view the wash process.



Door Lock Delay

In case of power failure, our heavy-duty stainless steel door can be easily opened without the aid of tools or an attendant. After a 60-second time delay has lapsed, customers can remove garments quickly and efficiently.

Superior Serviceability

Speed Queen's removable top and front panels are designed for minimum down time and ease of service. Now troubleshooting electrical systems as well as accessing drain valve components is easier than ever.



Reversing Wash Action

The alternate rotating wash action thoroughly cleans your customers clothes without damaging those delicate fabrics.

Low Water Usage

Speed Queen washer-extractors are designed to save water and energy. This translates into operational efficiency, satisfied customers, and more importantly, bottom line profits.

Heavy-Duty Bearings and Trunion Assembly

Sealed heavy-duty bearings require no lubrication — permanently!
(20 lb - 50 lb models only)

Control Option




Fully programmable
NetMaster™ control

Our advanced NetMaster™ control makes it easy for customers to locate the vend price, cycle selections, cycle status, and remaining cycle time. Customers will appreciate knowing the status of their laundry and the ability to be more efficient with their time.

Our use of international icons instruct users how to operate the unit. This eliminates time spent educating customers on basic operation and decreases misuse.

Activation Options



Coin Drop

Speed Queen lets you customize your activation options. Our coin drop, with its all-metal design, reduces coin jamming and provides superior coin validation.



Dual Coin Drop

Dual coin drop for International use and a USA dual coin conversion are also available.



World
Coin Drop

Speed Queen's World Drop uses electronic signature recognition technology for superior coin validation. The world drop comes pre-programmed to accept coins for your market. Additional coins or a metallic token can be added by the owner by using a unique and simple "Teach Mode".



Card Activated

CardMate Plus™ system offers the convenience and safety of a cashless operation.

(North America only)

Heating Options

Speed Queen offers electric or steam heating to boost or maintain wash temperatures.

3 YEAR WARRANTY

At Speed Queen, we're confident that our washer-extractors are built better to last longer and we're offering the following limited warranty to prove it:

Through three years*

Any part on the entire machine.

Through five years*

The bearings and bearing seal assembly. Frame, cylinder and shaft assembly.

* Parts only. Labor not included.
See Speed Queen Warranty Bond for specifics.

WASHER-EXTRACTOR SPECIFICATIONS

	SC20	SC25	SC30	SC40	SC60	SC80
Capacity	20 lb (9 kg)	25 lb (11 kg)	30 lb (14 kg)	40 lb (18 kg)	60 lb (27 kg)	80 lb (36 kg)
Width (in/mm)	26" (660 mm)	26" (660 mm)	29" (737 mm)	30 5/8" (778 mm)	34 1/16" (865 mm)	41 1/5" (1054 mm)
Depth (in/mm)	29 11/16" (754 mm)	33 11/16" (856 mm)	35" (889 mm)	40 1/4" (1022 mm)	42 4/5" (1086 mm)	51 5/8" (1311 mm)
Height (in/mm)	42" (1067 mm)	45" (1143 mm)	45" (1143 mm)	47 1/2" (1200 mm)	50" (1269 mm)	56" (1422 mm)
Cylinder Diameter (in/mm)	21" (533 mm)	21" (533 mm)	24" (610 mm)	26 1/4" (667 mm)	30" (762 mm)	36" (914 mm)
Cylinder Volume	2.76 cu. ft. (78.1 liters)	3.76 cu. ft. (106 liters)	4.19 cu. ft. (118 liters)	6.34 cu. ft. (180 liters)	9.0 cu. ft. (255 liters)	12.96 cu. ft. (367 liters)
Door Opening Size (in/mm)	12" (305 mm)	12" (305 mm)	14 11/32" (364 mm)	16 1/4" (413 mm)	16 1/4" (413 mm)	18 1/5" (470 mm)
Door Bottom to Floor (in/mm)	14 3/8" (366 mm)	14 3/8" (366 mm)	14" (356 mm)	14 1/2" (368 mm)	13 1/2" (343 mm)	17 3/4" (451 mm)
G-Factor (High Extract)	82	87	78	82	86	85/140
Wash Speed (rpm)	53	55	47	47	44	22/40
High Extract (rpm)	525	540	480	470	450	280/408/524
Water Inlet Conn. (in/mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)	.75" (19 mm)
Drain Diameter (in/mm)	2 3/8" (52 mm)	2 3/8" (52 mm)	2 3/8" (52 mm)	3" (76 mm)	3" (76 mm)	3" (76 mm)
Drain Height to Floor (in/mm)	4 3/8" (111 mm)	4 3/8" (111 mm)	4" (102 mm)	4 3/4" (121 mm)	3 1/2" (89 mm)	5 3/4" (146 mm)
Motor HP (wash)	.18 HP (.13 kW)	.25 HP (.19 kW)	.25 HP (.19 kW)	.40 HP (.30 kW)	.55 HP (.41 kW)	N/A
Motor HP (extract)	1.0 HP (.75 kW)	1.4 HP (1.04 kW)	1.4 HP (1.04 kW)	1.8 HP (1.3 kW)	2.7 HP (2.01 kW)	5 HP (3.7 kW)
Voltage/Hz/Phase* Circuit Breaker-FLA	110-120/60/1 20-15 amp	N/A	N/A	N/A	200-240/50-60/1-3 12-6.7 amp	N/A
Voltage/Hz/Phase* Circuit Breaker-FLA	208-240/60/1 20-10 amp	208-240/60/1 20-10 amp	208-240/60/1 20-10 amp	208-240/60/1 30-13.5 amp	208-240/60/3 20-10 amp	N/A
Voltage/Hz/Phase* Circuit Breaker-FLA	208-240/60/3 15-5 amp	208-240/60/3 15-6 amp	208-240/60/3 15-7 amp	208-240/60/3 20-7.5 amp	380/60/3 15-6 amp	200-240/50-60/3 20-12.4 amp
Voltage/Hz/Phase* Circuit Breaker-FLA	380/60/3 15-4 amp	380/60/3 15-4 amp	380/60/3 15-4 amp	380/60/3 15-5 amp	380-415/50/3 15-6 amp	N/A
Voltage/Hz/Phase* Circuit Breaker-FLA	380-415/50/3 15-4 amp	380-415/50/3 15-4 amp	380-415/50/3 15-4 amp	380-415/50/3 15-5 amp	220-240/50/3 20-10 amp	380-415/50-60/3 15-4.5 amp
Voltage/Hz/Phase* Circuit Breaker-FLA	220-240/50/3 15-5 amp	220-240/50/3 15-6 amp	220-240/50/3 15-6 amp	220-240/50/3 20-7.5 amp	380-415/50-60/3 15-4 amp**	N/A
Voltage/Hz/Phase* Circuit Breaker-FLA	220-240/50/1 20-10 amp	220-240/50/1 20-10 amp	220-240/50/1 20-10 amp	N/A	N/A	N/A
Voltage/Hz/Phase* Circuit Breaker-FLA	200/50/3 15-5 amp	200/50/3 15-6 amp	200/50/3 15-7 amp	200/50/3 20-7.5 amp	200/50/3 20-7.5 amp	N/A
Shipping Dimensions (in/mm)	H: 51" (1295 mm) W: 29" (737 mm) D: 32 1/2" (826 mm)	H: 53 1/2" (1359 mm) W: 29" (737 mm) D: 36 1/4" (921 mm)	H: 53 1/2" (1359 mm) W: 30 1/2" (775 mm) D: 37 1/2" (953 mm)	H: 56" (1422 mm) W: 32" (813 mm) D: 41" (1041 mm)	H: 58 1/2" (1486 mm) W: 36" (914 mm) D: 44 1/2" (1130 mm)	H: 62 1/2" (1588 mm) W: 48" (1219 mm) D: 56" (1422 mm)
Net Weight	390 lb (177 kg)	435 lb (198 kg)	495 lb (225 kg)	706 lb (321 kg)	826 lb (375 kg)	1406 lb (639 kg)
Standard Shipping Weight	410 lb (186 kg)	470 lb (214 kg)	535 lb (243 kg)	744 lb (338 kg)	881 lb (400 kg)	1456 lb (662 kg)
Wood Crate Shipping Weight	480 lb (218 kg)	530 lb (241 kg)	601 lb (273 kg)	846 lb (385 kg)	1020 lb (464 kg)	1506 lb (685 kg)
Agency Approvals	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc	ETL, CE, ETLc

* Standard domestic voltage 208-240/60/3. Circuit breaker and amp draw data shown is for standard voltage models without auxiliary heat. Consult factory for other configurations. Manufacturer strongly recommends using a circuit breaker instead of fuses. Use 3-pole circuit breakers for 3-phase machines. CE approval is available on 50 hz 20-60 models.

Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification. Features and certifications may vary by model.

© Copyright 2003 Alliance Laundry Systems LLC



www.speedqueen.com


Speed Queen
Alliance Laundry Systems

AC03-206