

FUJITSU



Mini-Split Air Conditioners and Heat Pumps for Residential and Light Commercial Applications





Halcyon 

*Where comfort and style meet
performance and reliability.*



TABLE OF CONTENTS

FEATURES

Mini-Splits Defined.....	4
Individual Zoning	6
Comfort Solution	8
Energy Efficient	9
Comfort & Convenience	10
Applications	11
Feature Descriptions	12

MODEL LINEUP

Indoor and Outdoor Model Table	14
--------------------------------------	----

SINGLE ZONE MINI-SPLITS

Wall Mount	17
Floor/Ceiling	23
Ceiling Suspended	23
Duct	24
Compact Cassette	26
Large Cassette	28

MULTI-ZONE MINI-SPLITS

Overview	31
Indoor Units	
Wall Mount	33
Duct	34
Compact Cassette	35
Multi-Zone (2-4 Zones) Outdoor	36
Flex-Zone (2-8 Zones) Outdoor	37
Branch Boxes	38
Wiring	40
Piping	41
Allowable Combinations	42

ACCESSORIES

Descriptions	44
Compatibility Chart	45

MISCELLANEOUS

Line Set Length Chart	46
Model Nomenclature	46



Fujitsu Mini-Splits: Year-Round, Whole-Home or Business Energy Efficient Heating and Cooling

What is a Mini-Split?


Halcyon systems eliminate the need for a basement or attic-located evaporator unit and bulky ductwork by using thin copper tubing that pumps refrigerant directly to discreet wall mounted or concealed units inside. Even more remarkable, this same unit works in reverse in winter, absorbing heat from the outside air and moving it indoors to heat your home. The result? Efficient cooling and heating for year-round, whole-house comfort in most climates.

Available in numerous mix-and-match capacities and configurations, there's a Halcyon mini-split system for even the most difficult to heat and cool areas.




How Does a Mini-Split Work?

Like your refrigerator, heat pumps use electricity to pump refrigerant and transfer heat from one space to another. When we transfer heat from within our home to the outdoors, we call it "air conditioning". Conversely, when we transfer heat from the outdoors to within the home, we call it a "heat-pump".




Heat Pumps Provide Heat When it is Chilly

Because refrigerant is naturally much colder than outdoor temperatures even on a very cold day, it actually absorbs heat from outdoors, and transfers the heat it absorbs outside to within your home. The refrigerant's physical properties do this naturally. What you pay for is the electricity to pump refrigerant via copper tubing from outdoors to indoors. Because we move the heat rather than create it (as electric baseboard or resistant heat does), we can deliver up to 4 times the heat for the energy we consume!




Air Conditioners Provide Cooling When It's Warm

Come spring and summer, simply reverse the process and put the same system into "cooling mode" and transfer heat from indoors to the outside. For many climates, the advanced technology that goes into these units creates a far more cost effective alternative to either gas or oil-fired units for heat, or a central ducted system for air conditioning. Fujitsu's mini-splits come in both cooling-only models or heat pumps, which provide both heating and cooling.



Electric Heaters versus Heat Pumps



An electric heater converts electricity directly to heat, and if we assume that the heat loss is zero, the output from one kilowatt input is one kilowatt or 3,400 BTU and the EER is 3.4.




Heat pumps are more efficient than some other forms of heating because heat pumps do not actually create heat - they just move it from one place to another. For example, the output of an efficient 10 EER heat pump is triple that of an electric heater.

*EER (Energy Efficiency Rating) = Rated BTU capacity divided by total kW input.

Individual Zoning: Personalized Whole Home Comfort

Halcyon HFI Systems are some of today's most advanced forms of heating and air conditioning. One outdoor unit can operate up to 8 indoor units simultaneously. Fujitsu's HFI Systems are super quiet as well as highly energy efficient.


- Each indoor unit can be operated independently via remote control
- Choose from a variety of indoor unit styles
- Provide both heating and cooling (not simultaneously)
- High energy efficiencies
- Quiet operation



Wall Mounted

Stylish, slim and elegant, wall mounted units are designed to complement any interior décor.

- Compact size
- Wireless remote control
- Automatic swinging louvers



Shown here is a 3-zone system using outdoor unit AOU36RLXFZ.



Compact Duct

Mounted in a ceiling or in a framed enclosure below a ceiling. They use minimal ductwork and remain very energy efficient.

- Concealed and out of sight
- Look of central air with the efficiency of a mini-split
- Less ducts = higher efficiency

Wall Mounted

They mount high on a wall, out of sight and do not require ductwork, increasing energy efficiency.

- Quiet operation
- Easy maintenance
- High delivered efficiency means lower utility bills



Compact Cassette

Cassettes are extremely discreet, with only the grille showing in the ceiling. They use the latest fan technology to distribute the conditioned air evenly.


- Wired remote controller (wireless is optional)
- Powerful turbo fan operation
- Fits into a standard 2' x 2' ceiling grid

A Solution for All of Your Comfort Needs

Ductless Technology

Don't waste money cooling and heating the ducts in your walls and attic. Fujitsu systems are ductless, meaning they install easily and won't take up valuable closet space. Since mini-splits have little to no ducting, they forego those energy losses typically associated with central forced-air systems. Duct losses in a central air system can easily account for more than 30% of energy consumption, especially if the ducts are not sealed tight or in an unconditioned space such as an attic or crawlspace.

Central Air System versus Fujitsu HFI Quad Zone




Thick black lines represent ducts of a Central Air System.

Red lines represent mini-ducts of a Fujitsu Quad Zone Compact Duct System.

Whole Home or Business Comfort

Fujitsu's Halcyon HFI systems provide home and business owners just the right amount of heating and cooling needed by installing 2 to 8 indoor units connected to one outdoor unit. Indoor units vary by size and style and each creates its own "zone" of comfort, allowing you to heat or cool individual rooms, hallways and open spaces.



A Year Round Solution

Revolutionary Halcyon heat pumps provide both heating and cooling for year round comfort in most climates. A simple push of a button on the remote control allows you to switch from heating to cooling (or vice versa) automatically.



Energy Efficient: The Smart Choice in Comfort


As much as half of the energy used in your home goes to heating and cooling. So, making smart decisions about your home's heating and air conditioning system can have a big effect on your utility bills — and your comfort.

Where Does My Money Go?



The high energy efficiencies of Halcyon systems slash utility bills by up to 25%. If your average annual utilities are \$4,200, Fujitsu can save you up to \$1,050 annually or \$10,500 in 10 yrs!*

*Savings may vary based on model selected, hours of operation and geographical location. Example given based on 26-SEER system versus 13-SEER system.



Rebates

To encourage customers to buy energy efficient products, many local utility companies offer significant rebates for the purchase of a ductless mini-split system. Go to Fujitsu's web site to search for local rebates, consumer loans and utility bill discounts. We provide a listing of rebates and offerings on qualifying Fujitsu mini-splits by state. www.fujitsugeneral.com/utility_rebates.htm



Federal Tax Credit Up To \$300 through 2013


A tax credit can provide significant savings. It reduces the amount of income tax you have to pay. Unlike a deduction, which reduces the amount of income subject to tax, a tax credit directly reduces the tax itself.

- Federal tax credits are effective for systems purchased through December 31, 2013 for "Qualified Energy Property"
- The federal tax credit for qualified equipment is 10% of the amount paid but shall not exceed \$300 for the qualified energy property.
- Fujitsu has 16 qualifying systems in 2013
- Check with your tax professional for details and visit www.energystar.gov and click on "Tax Credits" for additional information.

Comfort and Convenience

Flexible and Quiet

Mini splits offer flexibility because they can be suspended from a ceiling, mounted flush behind a drop ceiling, hung on a wall or floor-standing. Ductless heat pumps allow for a peaceful inside environment by enabling the contractor to install components like compressors and motors outdoors.




Constant Comfort through Inverter Technology


Inverter technology is like cruise control for your heating or cooling system. Compressors only run as fast as they need to handle the cooling or heating demand. They can handle greater extremes in temperature, are smoother and more stable in operation, and reach the desired temperature more quickly than conventional air conditioners.

Inverter Benefits

- More heat at lower outdoor temperatures
- Lower RPMs = quieter operation
- Desired temperature in half the time
- Up to 30% more efficient
- Stable temperature



Conventional System



Inverter System



User Friendly Control

Fujitsu is using ergonomics to expand the use of user friendly designs such as easy-to-read large LCD displays, easy-to-operate buttons, and displays with easily recognizable colors and icons. We are producing control systems that provide greater convenience for both individual and centralized control with operability suitable for the application.



Optional Wired Remote UTY-RVNUM

Standard Wireless Remote for RLS2 and RLS2H Systems



Applications



Where can mini-splits be used?

- Convenience stores
- Fast food chains
- Fire houses
- Police stations
- Oil rigs
- Bars
- Sunrooms and additions
- Warehouses
- Nursing homes
- Small offices
- Older homes
- New construction homes
- Schools
- Places of worship
- Hospitals and medical facilities
- Restaurants
- Computer rooms
- Hotels and motels
- Car washes
- ATM vestibules

Just about any place that requires comfort!



Feature Explanation

SEER

Seasonal Energy Efficiency Rating. Used to express efficiency of an AC or Heat Pump. A higher rating means more efficient.

HSPF

Heating Seasonal Performance Factor, measures the efficiency of heating portion of your heat pump.



ENERGY STAR® Qualified

Qualified products and practices help you save money and reduce greenhouse gas emissions by meeting strict energy efficiency guidelines set by the U.S. Environmental Protection Agency and the U.S. Department of Energy.



Apple Catechin Filter (polyphenol ingredient from apples)

Dust, mold spores and microorganisms are absorbed onto the filter by static electricity and growth is inhibited and deactivated. 3 - 12 month life expectancy, depending on environment.



Ion Deodorizing Filter

Deodorizes by decomposing absorbed odors using the oxidizing and reducing effects of ions generated by fine ceramic particles. 3 year life expectancy. Wash to restore surface action.



Sleep Timer

Automatically adjusts the temperature while you sleep to make you more comfortable.



24 Hour Timer

Allows for one on/off cycle during a 24 hour period.



Weekly Timer

Allows you to set on/off time twice a day and a different on/off time by day.



Dry Mode

Helps reduce humidity levels when cooling requirements are low.



Auto Louver: Up/Down

Redirects airflow automatically with seven position up and down motion which can be set to auto swing.



Auto Louver: 4 Way

Redirects airflow automatically with up/down and left/right motion.



Auto Fan Mode

System starts in high fan speed and automatically adjusts downward as room begins to reach set temperature.



Powerful Operation

20 minutes of continuous operation at maximum airflow and maximum compressor speed. Rapid cooling and heating makes the room comfortable quickly.



Minimum Heat Mode

Sets room temperature to 50°F, keeping temperatures above freezing and reducing power consumption.



Economy Mode

Thermostat setting automatically changes according to the temperature to avoid unnecessary cooling and heating.



Energy Saver

Keeps room cool enough for comfort by using a relaxed thermostat setting reducing power consumption.



Energy Saving Program (ESP)

If a space is left without turning the unit off, ESP knows that it is unoccupied and 20 minutes later, temperature is adjusted accordingly until users return to the room.

+Function is bypassed during defrost and at low speed operation. This feature may limit cooling/heating capacity during high/low ambient conditions and increase energy consumption as system may need to operate longer due to reduced compressor speed.



Quiet Mode (Indoor Unit)

An extra quiet fan speed to make sure you are not disturbed.



Outdoor Unit Low Noise

Limits compressor and fan speed during high speed operation for a 3 dB noise reduction.+



Power Diffuser

An additional louver that opens based on monitoring sensors to quickly enhance immediate comfort needs.



Auto Restart/Reset

Following a power failure, systems will automatically restart in the same operating mode as before, once power has been restored.



Auto Changeover (heating to cooling or vice-versa)

Automatically alternates between heating or cooling if the room temperature falls 4°F below the set temperature when cooling or rises 4°F above set temperature when heating.*



Low Ambient Cooling

Can operate in cooling mode even when outdoor ambient is 0°F, 14°F or 32°F, depending on model, without modification. Operation outside of factory specification is not recommended.



Cold Prevention

Indoor coil will warm prior to fan operating, preventing cold air during heating mode.



Slender Fit

Cassette body can be moved downward into the room 1-3/8" to accommodate limited ceiling space.



Remote Temperature Sensor

Room temperature sensor is located in optional wired remote controller only.



Pump Down Operation

Collects all refrigerant in system back into the outdoor unit when the unit is to be moved or before servicing the refrigerant circuit.



Daisy Chain

Ability to connect up to 16 identical style indoor units to one wired remote.



High Ceiling Mode

Temperature at the top of a high ceiling room may be warmer than the space occupied; this mode adjusts for this difference.



Branch Duct Capable

Systems are capable of attaching field-supplied branch ducts providing up to 38% of the cooling up to 16 feet away.



Fresh Air Intake

Outside air can be introduced by attaching field supplied flexible duct to fresh air knockouts.



Base Pan Heater

Prevents condensate from freezing on the outdoor unit.



Third Party Device Control

Turns system on or off using a normally closed circuit. Interface with third party devices such as home automation.



Warranty

Fujitsu systems come with either a 2 Year Parts / 6 Year Compressor warranty or a 5 Year Parts / 7 Year Compressor warranty.















*Auto Changeover is not designed to provide rapid changes between heating and cooling operation or simultaneous heating and cooling. This feature is not recommended for systems with more than one indoor unit unless all indoor units have similar heating and cooling requirements and have similar temperature set points. If all indoor units have similar heating and cooling requirements and have similar temperature set points, auto changeover will work.
















Feature Summary

	Single Zone Wall Mount Heat Pumps										Single Zone Wall Mount Cooling	Single Zone Ducted	Single Zone Cassette	Universal Ceiling Susp.	Large Cassette	HFI Multi-Zone and Flex-Zone																						
	9RL2	9RLF2	9RLS2	9RLS2H	12RL2	12RLF2	12RLS2	12RLS2H	15RLS2	15RLS2H	18RLXFW	24RLXFW	30RLX	18CL	24CL1	30CLX1	36CLX1	9RLFCD	12RLFCD	18RLFCD	9RLFCC	12RLFCC	18RLFCC	18RULX	24RULX	36RSLX	18RCLX	24RCLX	36RCLX	42RCLX	HFI: Small Wall (7, 9, 12k BTU)	HFI: Designer Wall (9, 12, 15k BTU)	HFI: Large Wall (18, 24k BTU)	HFI: Cassette	HFI: Compact Duct			
SEER	16.0	11.0	12.5	8.8	9.0	11.0	12.0	9.3	12.0	10.3	10.0	9.5	-	-	-	-	-	12.2	11.5	11.3	13.0	12.2	11.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.8'	9.8'	9.8'	9.8'	9.3'			
HSPF	9.0	11.0	12.5	8.8	9.0	11.0	12.0	9.3	12.0	10.3	10.0	9.5	-	-	-	-	-	12.2	11.5	11.3	13.0	12.2	11.5	8.5	8.5	8.5	8.5	8.5	8.5	8.5	9.8'	9.8'	9.8'	9.8'	9.3'			
ENERGY STAR® Qualified		●	●	●	●	●	●	●	●	●	●	●	●					●	●	●	●	●	●								●*	●	●	●	●			
Apple Catechin Filter		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Ion Deodorizing Filter		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Sleep Timer	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
24 Hour Timer		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Weekly Timer		□	●	●	□	●	●	●	●	●	□	□	□	□	□	□	□	□	●	●	●	●	●	□	□	□	●	●	●	●	●	□	●	□	●	●		
Dry Mode	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Auto Louver: Up/ Down	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Auto Louver: 4 Way											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		
Auto Fan Mode	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Powerful Operation	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Minimum Heat Mode		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	
Economy Mode	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Energy Saver																							□	□	□	●	●	●	●	●	●	●	●	●	●	●		
Energy Saving Program (ESP)		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Quiet Mode (Indoor Unit)	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Outdoor Unit Low Noise		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Power Diffuser											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Auto Restart/Reset	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Auto Changeover	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Low Ambient Cooling	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
0-Degree Ambient Cooling											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Long Piping Length (165'+)											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Cold Prevention	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Slender Fit																																						
Remote Temperature Sensor		□*	□*	□*	□*	□*	□*	□*	□*	□*	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	□	
Daisy Chain																			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Pump Down Operation											●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
High Ceiling Mode																			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Branch Duct Capable																																						
Condensate Pump																			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Fresh Air Intake																			●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
Base Pan Heater			●				●	●																														
Third Party Device Control**		○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
Warranty: 6 Yr Compressor / 2 Yr Parts																																						
Warranty: 7 Yr Compressor / 5 Yr Parts	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●

^ SEER and HSPF ratings depend on combination of indoor units and outdoor unit selected.
 □ Available only with optional wired remote controller. □* Available only with optional wired remote controller and optional Interface Kit.
 ▲ Available only with optional wireless remote controller. ○ Available only with optional Interface Kit.
 ♦ Available only with optional Fresh Air Intake Kit. * Available only when used with Flex Zone AOU48RLXFZ1 outdoor unit.
 * The only combinations that qualify are AOU18RLXFZ with (2) ASU9RLF, AOU18RLXFZ with (1) ASU7RLF + (1) ASU12RLF, AOU18RLXFZ with (1) ASU9RLF + (1) ASU12RLF, AOU24RLXFZ with (2) ASU7RLF + (1) ASU9RLF.
 ** Operation monitoring and On/Off control only.
 + Auto Changeover is not designed to provide rapid changes between heating and cooling operation or simultaneous heating and cooling. This feature is not recommended for systems with more than one indoor unit unless all indoor units have similar heating and cooling requirements and have similar temperature set points. If all indoor units have similar heating and cooling requirements and have similar temperature set points, auto changeover will work.

Single Zone And Multi-Zone Systems Lineup




SINGLE ZONE MINI-SPLITS				
BTU	9,000	12,000	15,000	
Wall Mount 115V Inverter	 ASU9RL2 / AOU9RL2	 ASU12RL2 / AOU12RL2		
Wall Mount High SEER	 ASU9RLS2 / AOU9RLS2	 ASU12RLS2 / AOU12RLS2	 ASU15RLS2 / AOU15RLS2	
Wall Mount Extra Low Temp Heating	 ASU9RLS2 / AOU9RLS2H	 ASU12RLS2 / AOU12RLS2H	 ASU15RLS2 / AOU15RLS2H	
Wall Mount Heat Pump	 ASU9RLF / AOU9RLF	 ASU12RLF / AOU12RLF		
Wall Mount Cooling Only				
Universal Mount Floor/Ceiling				
Ceiling Suspended				
Compact Duct	 ARU9RLF / AOU9RLF	 ARU12RLF / AOU12RLF		
Compact Cassette	 AAU9RLF / AOU9RLF	 AAU12RLF / AOU12RLF		
Large Cassette				

MULTI ZONE MINI-SPLITS - INDOOR UNITS						
BTU	7,000	9,000	12,000	15,000	18,000	24,000
Compact Wall Mount	 ASU7RLF	 ASU9RLF	 ASU12RLF			
Designer Series Wall Mount		 ASU9RLS2	 ASU12RLS2	 ASU15RLS2		
Large Wall Mount					 ASU18RLF	 ASU24RLF
Compact Duct		 ARU9RLF	 ARU12RLF		 ARU18RLF	 ARU24RLF
Compact Cassette		 AAU9RLF	 AAU12RLF		 AAU18RLF	

★ Indicates system is ENERGY STAR® Qualified in 2013. 💰 Indicates system qualifies for Federal Tax Credit in 2013.

	18,000	24,000	30,000	36,000	42,000
	 ASU18RLF / AOU18RLXFW	 ASU24RLF / AOU24RLXFW	 ASU30RLX / AOU30RLX		
	 ASU18CL / AOU18CL	 ASU24CL1 / AOU24CL1	 ASU30CLX1 / AOU30CLX1	 ASU36CLX1 / AOU36CLX1	
	 ABU18RULX / AOU18RLX	 ABU24RULX / AOU24RLX			
				 ABU36RSLX / AOU36RLX	
	 ARU18RLF / AOU18RLFC				
	 AAU18RLF / AOU18RLFC				
	 AAU18RCLX / AOU18RLX	 AAU24RCLX / AOU24RLX		 AAU36RCLX / AOU36RLX	 AAU42RCLX / AOU42RLX

MULTI ZONE MINI-SPLITS - OUTDOOR UNITS

BTU	18,000	24,000	36,000	48,000
2 Indoor Units	 AOU18RLXFZ			
2 - 3 Indoor Units		 AOU24RLXFZ		
2* - 4 Indoor Units			 AOU36RLXFZ	
2 - 8 Indoor Units				 AOU48RLXFZ1

* If AOU36RLXFZ is paired with two 18,000 BTU indoor units, you have to purchase optional kit Part #K9FZ1818.
 + The only combinations that qualify are AOU18RLXFZ with (2) ASU9RLF, AOU18RLXFZ with (1) ASU7RLF + (1) ASU12RLF, AOU18RLXFZ with (1) ASU9RLF + (1) ASU12RLF, AOU24RLXFZ with (2) ASU7RLF + (1) ASU9RLF.

SINGLE ZONE MINI-SPLIT SYSTEMS

*Making the hottest places
cool and the coolest places
more comfortable*

- Extensive lineup from 9,000 to 42,000 BTU/h
- 30 different systems available in 10 indoor unit styles
- Energy efficient systems with SEER ratings as high as 27.2 and HSPF as high as 13.0
- 15 ENERGY STAR® Qualified systems
- Inverter Technology is used in all systems
- All systems feature environmentally friendly R410A refrigerant
- Quiet operation with indoor units as low as 21 dB and outdoor units as low as 47 dB



Wall Mounted 115V Inverter 9, and 12,000 BTU Systems

SYSTEMS 9RL2, 12RL2



16.0 SEER

Function

Stylish, slim and elegant, these popular wall mounted units are designed for single rooms. Indoor units have a clean, aesthetic design and are small but mighty and shorter in length than competing units, helping them blend into any room. These 16-SEER heat pump systems now feature Inverter technology, environmentally friendly R410A refrigerant, both heating and cooling operation, quiet mode and easy maintenance.

Applications

This category of equipment is ideal for smaller spaces where spot cooling or heating is required. Residential applications including sunrooms and additions are made easier with these 115 volt heat pumps. Do you have a warm or cool spot in your home? Fujitsu mini-splits can provide extra cooling or heating capacity for those hard to cool areas. Commercially, their small size makes them ideal for small offices, providing individual temperature control.

Easy Maintenance

Front panel is easily removed for cleaning.



Standard Features

- Wireless Remote Control
- Sleep Timer
- Dry Mode
- Auto Louver
- Auto Mode
- Powerful Operation
- Quiet Mode
- Economy Mode
- Auto Restart/Reset
- Auto Changeover
- Low Ambient
- Cold Prevention



	9RL2 Heat Pump	12RL2 Heat Pump
Nominal Cooling BTU/h	9,000	12,000
Nominal Heating BTU/h	10,000	14,000
HSPF BTU/hW	9.0	9.0
SEER BTU/hW	16.0	16.0
EER Clg/Htg	10.8/13.0	10.0/11.5
Clg. Operating Range °F(°C)	15~115 (-10~46)	15~115 (-10~46)
Htg. Operating Range °F(°C)	15~75 (-10~24)	15~75 (-10~24)
Moisture Removal Pt./h(l/h)	1.3 (2.7)	1.8 (3.8)
Voltage/Frequency/Phase	115/60/1	115/60/1
Recommended Fuse Size (A)	15	20
Air Circ. C.F.M. (m ³ /h): Hi	436 (740)	436 (740)
Medium	353 (600)	353 (600)
Low	265 (450)	265 (450)
Quiet	191 (325)	191 (325)
Noise Level dB(A) Clg/Htg: Hi	43/43	43/43
Medium	38/38	38/38
Low	33/33	33/33
Quiet	23/23	23/23
Outdoor Fan Speed RPM	730	860
Outdoor Noise Level dB(A) Clg/Htg	47/48	51/51
Current (A): Cooling	7.5	10.9
Heating	7.0	11.0
Power Use (kw): Cooling	0.83	1.20
Heating	0.77	1.21
Fan Speeds Stage	4 + Auto	4 + Auto
Air Direction: Horizontal	Manual	Manual
Vertical	Automatic	Automatic
Air Filter	Washable	Washable
Connection Method	Flare	Flare
Combined Min. Lgth Ft (m)	9 (2.7)	9 (2.7)
Combined Max. Lgth Ft (m)	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)
Conn. Pipe Diameter Inch	Suc. 3/8 Dis. 1/4	Suc. 3/8 Dis. 1/4
Net Weight lbs. (kg)	16 (7)	64 (29)
Dimensions: Height Inch	10-5/16	21-1/4
mm	262	540
Width Inch	32-9/32	26
mm	870	660
Depth Inch	8-1/8	11-11/32
mm	206	290
Refrigerant	R410A	R410A

Note: Figures are based on 115 Volts.

Indoor ASU9RL2
Outdoor AO9RL2
Indoor ASU12RL2
Outdoor AO12RL2



Wall Mounted High-SEER 9, 12 and 15,000 BTU Systems

SYSTEMS 9RLS2, 12RLS2, 15RLS2



Federal Tax Credit Qualified
See Page 9 for details

Systems 9RLS2 and 12RLS2 only.



Up to 27.2 SEER

ESP Energy Saving Program

These Halcyon systems know how to save you money even when you forget. If you leave the room without turning the unit off, ESP knows that you left and 20 minutes later, set temperature is increased by 4°F when cooling and reduced by 8°F when heating. When you come back to the room, it returns to previous operating mode. This prevents wasteful operation to save energy without you having to think about it. This feature can be deactivated if chosen.



High Performance Heating

Heating capacity at low outdoor temperatures was improved by adopting a large heat exchanger and a high capacity compressor. Rated heating capacity is maintained up to 20°F. This new model can operate down to -5°F.

Standard Features for RLS2 and RLS2H Models

- Wireless Remote Control
- Economy Mode
- Apple Catechin Filter
- Energy Saving Program
- Ion Deodorizing Filter
- Quiet Mode (Indoor)
- Sleep Timer
- Low Noise Mode
- 24 Hour Timer
- Auto Restart/Reset
- Weekly Timer
- Auto Changeover
- Dry Mode
- Low Ambient Cooling
- Auto Louver: Up/Down
- Cold Prevention
- Auto Mode
- Remote Temp. Sensor*
- Powerful Operation Mode
- 3rd Party Device Control+
- Minimum Heat (50°F/10°C)

* Available only with optional wired remote controller and optional interface kit.
+ Available only with optional interface kit. Operation monitoring and On/Off control only.

Optional Accessories

- Wired Remote Controller: UTY-RVNUM
Backlit and includes room temperature
- Wired Remote Controller: UTY-RNNUM
- Simple Remote Controller: UTY-RSNUM
- Communication Kit: UTY-TWBXF



Systems 9RLS2, 12RLS2

	9RLS2 Heat Pump	12RLS2 Heat Pump	15RLS2 Heat Pump
Nominal Cooling BTU/h	9,000	12,000	14,500
Min.~Max. Cooling BTU/h	3,100~12,000	3,100~13,600	3,100~18,400
Nominal Heating BTU/h	12,000	16,000	18,000
Min.~Max. Heating BTU/h	3,100~22,000	3,100~22,100	3,100~23,900
HSPF BTU/hW	12.5	12.0	12.0
SEER BTU/hW	27.2	25.0	21.5
EER Clg/Htg	16.1/15.0	13.8/13.3	12.0/13.3
Clg. Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Htg. Operating Range °F(°C)	-5~75 (-21~24)	-5~75 (-21~24)	-5~75 (-21~24)
Moisture Removal Pt./h(l/h)	2.75 (1.3)	3.8 (1.8)	4.44 (2.1)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	20	20	20
Air Circ. C.F.M. (m ³ /h): Hi	500 (850)	500 (850)	530 (900)
Medium	394 (670)	394 (670)	436 (740)
Low	324 (550)	324 (550)	336 (570)
Quiet	194 (330)	194 (330)	229 (390)
Noise Level dB(A): Hi	43/43	43/43	45/45
Medium	37/38	37/38	40/40
Low	32/32	32/32	33/34
Quiet	21/21	21/21	25/27
Outdoor Fan Speed RPM Clg/Htg	780/780	870/780	870/780
Outdoor Noise Level dB(A)	48/49	49/50	51/51
Current Rated (A): Cooling	2.7	4.0	5.5
Heating	3.7	5.5	6.1
Power Use Rated (kw): Cooling	.56	.87	1.21
Heating	.80	1.20	1.35
Fan Speeds Stage	4+Auto	4+Auto	4+Auto
Air Direction: Horizontal	Manual	Manual	Manual
Vertical	Auto	Auto	Auto
Air Filter	Washable	Washable	Washable
Apple Catechin Filter	Yes	Yes	Yes
Connection Method	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	9 (2.7)	9 (2.7)	9 (2.7)
Combined Max. Lgth Ft (m)	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)	49 (15)
Conn. Pipe Diameter Inch	Suc. 3/8 Dis. 1/4	Suc. 3/8 Dis. 1/4	Suc. 1/2 Dis. 1/4
Net Weight lbs. (kg)	21 (9.5)	88 (40)	21 (9.5)
Dimensions: Height Inch	11-1/8 13-1/4*	24-13/32 11-1/8 13-1/4*	24-13/32 11-1/8 13-1/4*
mm	282/337*	620 282/337*	620 282/337*
Width Inch	34-1/4	31-3/32	34-1/4
mm	870	790	870
Depth Inch	7-1/4	11-13/32	7-1/4
mm	185	290	185
Refrigerant	R410A	R410A	R410A

Note: Figures are based on 230 Volts. *Height when front panel is open.

Wall Mounted High-Heat 9, 12 and 15,000 BTU Systems

SYSTEMS 9RLS2H, 12RLS2H, 15RLS2H



Federal Tax Credit Qualified
See Page 9 for details
Systems 9RLS2H and 12RLS2H only.



Up to 27.2 SEER

ESP Energy Saving Program

ESP senses when you leave a room and 20 minutes later, set temperature is increased by 4°F when cooling and reduced by 8°F when heating. When you come back to the room, it returns to previous operating mode. This feature can be deactivated if chosen.

High Performance Heating

Heating capacity at low outdoor temperatures was improved by adopting a large heat exchanger, a high capacity compressor, and a base heater for the outdoor unit. Rated heating capacity is maintained up to 20°F. RLS2H models can operate down to -15°F.

Base Freeze Prevention

- Equipped with a base heater that prevents condensate from freezing
- Cultivated base design discharges melted water through many holes.
- Without a heater, freezing condensate can cause noise, damage to fan blade, condenser, and system performance



Drain hole is not filled, no freezing of base | Freezing where there is no heater | Drain hole is closed, large freezing of base

Condition: Indoor temp. of 68°FDB / outdoor temp. of 5°FDB, Heating mode, High airflow volume. Operation for 24 hours.

Optional Accessories

- Wired Remote Controller: UTY-RVNUM
Backlit and includes room temperature!
- Wired Remote Controller: UTY-RNNUM
- Simple Remote Controller: UTY-RSNUM
- Communication Kit: UTY-TWBXF



	9RLS2H Heat Pump	12RLS2H Heat Pump	15RLS2H Heat Pump
Nominal Cooling BTU/h	9,000	12,000	14,500
Min.~Max. Cooling BTU/h	3,100~12,000	3,100~13,600	3,100~18,400
Nominal Heating BTU/h	12,000	16,000	18,000
Min.~Max. Heating BTU/h	3,100~22,000	3,100~22,100	3,100~23,900
HSPF BTU/hW	8.8	9.3	10.3
SEER BTU/hW	27.2	25.0	21.5
EER Clg/Htg	16.1/15.0	13.8/13.3	12.0/13.3
Clg. Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Htg. Operating Range °F(°C)	-15~-75 (-26~-24)	-15~-75 (-26~-24)	-15~-75 (-26~-24)
Moisture Removal Pt./h(l/h)	2.75 (1.3)	3.8 (1.8)	4.44 (2.1)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	15	15	20
Air Circ. C.F.M. (m ³ /h): Hi	500 (850)	500 (850)	530 (900)
Medium	394 (670)	394 (670)	436 (740)
Low	324 (550)	324 (550)	336 (570)
Quiet	194 (330)	194 (330)	229 (390)
Noise Level dB(A): Hi	43/43	43/43	45/45
Medium	37/38	37/38	40/40
Low	32/32	32/32	33/34
Quiet	21/21	21/21	25/27
Outdoor Fan Speed RPM Clg/Htg	780/780	870/780	870/780
Outdoor Noise Level dB(A)	48/49	49/50	51/51
Current Rated (A): Cooling	2.7	4.0	5.5
Heating	3.7	5.5	6.1
Power Use Rated (kw): Cooling	.56	.87	1.21
Heating	.80	1.20	1.35
Fan Speeds Stage	4+Auto	4+Auto	4+Auto
Air Direction: Horizontal	Manual	Manual	Manual
Vertical	Auto	Auto	Auto
Air Filter	Washable	Washable	Washable
Apple Catechin Filter	Yes	Yes	Yes
Connection Method	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	9 (2.7)	9 (2.7)	9 (2.7)
Combined Max. Lgth Ft (m)	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)	49 (15)
Conn. Pipe Diameter Inch	Suc. 3/8 Dis. 1/4	Suc. 3/8 Dis. 1/4	Suc. 1/2 Dis. 1/4
Net Weight lbs. (kg)	21 (9.5) 88 (40)	21 (9.5) 88 (40)	21 (9.5) 88 (40)
Dimensions: Height Inch	11-1/8 13-1/4*	24-1/2 13-1/4*	11-1/8 13-1/4*
mm	282/337*	620 282/337*	282/337* 620
Width Inch	34-1/4	31-3/32	34-1/4
mm	870	790	870
Depth Inch	7-1/4	11-13/32	7-1/4
mm	185	290	185
Refrigerant	R410A	R410A	R410A
Indoor	ASU9RLS2	ASU12RLS2	ASU15RLS2
Outdoor	AOU9RLS2H	AOU12RLS2H	AOU15RLS2H

Note: Figures are based on 230 Volts. *Height when front panel is open.

Wall Mounted HFI Single Zone 9, 12, 18 and 24,000 BTU

9RLFW, 12RLFW, 18RLXFW, 24RLXFW
(COMPATIBLE ONLY WITH HFI WALL MOUNT UNIT)



Standard Features

- Wireless Remote Control
- Apple Catechin Filter
- Ion Deodorizing Filter
- Sleep Timer
- 24-Hour Timer
- Weekly Timer*
- Dry Mode
- Auto Louver: Up/Down+
- Auto Louver: 4-way^
- Auto Mode
- Minimum Heat Mode
- Economy Mode
- Quiet Mode
- Power Diffuser^
- Auto Restart/Reset
- Auto Changeover
- Low Ambient Cooling
- Long Piping Length^
- Cold Prevention
- Remote Temp. Sensor*
- Pump Down Operation^
- 3rd Party Device Control**

* Available only with optional wired remote controller.
 + Feature of 9RLFW and 12RLFW only.
 ^ Feature of 18RLXFW and 24RLXFW only.
 ** Operation monitoring and On/Off control only.

Optional Accessories

- Wired Remote Controller: UTY-RVNUM
Backlit and includes room temperature
- Wired Remote Controller: UTY-RNNUM
- Simple Remote Controller: UTY-RSNUM
- Communication Kit: UTY-TWBXF

#Adapter Fittings

Supplied in outdoor unit to be installed on the indoor unit.



Federal Tax Credit Qualified
See Page 9 for details

	9RLFW	12RLFW	18RLXFW	24RLXFW
	Heat Pump	Heat Pump	Heat Pump	Heat Pump
Nominal Cooling BTU/h	9,000	12,000	18,000	22,000
Min.~Max. Cooling BTU/h	1,700~10,900	3,100~13,300	7,000~23,000	9,900~27,300
Nominal Heating BTU/h	12,000	16,000	21,600	27,600
Min.~Max. Heating BTU/h	1,700~15,000	3,100~19,100	7,000~29,000	7,500~36,200
HSPF BTU/hW	11.0	11.0	10.0	10.0
SEER BTU/hW	23.0	22.0	19.2	18.0
EER Clg/Htg	13.8/13.47	12.5/12.5	13.3/12.0	12.5/11.6
Clg. Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)	0~115 (-18~46)
Htg. Operating Range °F(°C)	5~75 (-15~24)	5~75 (-15~24)	5~75 (-15~24)	0~75 (-18~24)
Moisture Removal Pt./h(l/h)	2.75 (1.3)	3.80 (1.8)	5.9 (2.8)	6.3 (3.0)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	15	20	20	30
Air Circ. C.F.M. (m³/h): Hi	353 (600)	388 (660)	541 (920)	659 (1,120) Clg 677 (1,150) Htg
Medium	306 (520)	330 (560)	435 (740)	500 (930)
Low	253 (430)	265 (450)	365 (620)	435 (740)
Quiet	200 (340)	200 (340)	306 (520) Clg 318 (540) Htg	365 (620)
Noise Level dB(A) (Clg/Htg): Hi	37/37	40/40	43/44	49/49
Medium	33/33	36/36	37/37	42/42
Low	29/29	30/31	33/33	37/37
Quiet	25/25	25/25	28/28	33/33
Outdoor Fan Speed RPM Clg/Htg	810/780	870/780	620/620	800/850
Outdoor Noise Level dB(A) Clg/Htg	48/48	49/49	47/50	54/55
Current Rated/Max (A): Cooling	3.2/6.0	4.4/6.5	6.2/13.5	7.9/15.0
Heating	4.2/7.5	5.9/9.0	8.0/14.5	10.5/15.5
Power Use Rated/Max (kw): Cooling	0.65/1.27	0.96/1.40	1.35/3.01	1.76/3.42
Heating	0.89/1.60	1.28/1.99	1.80/3.23	2.38/3.53
Fan Speeds Stage	4+Auto	4+Auto	4+Auto	4+Auto
Air Direction: Horizontal	Manual	Manual	Automatic	Automatic
Vertical	Automatic	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable	Washable
Apple Catechin Filter	Yes	Yes	Yes	Yes
Connection Method	Flare	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	9 (2.7)	9 (2.7)	16 (5)	16 (5)
Combined Max. Lgth Ft (m)	66 (20.1) (pre-charge: 49')	66 (20.1) (pre-charge: 49')	164 (50) (pre-charge: 66')	164 (50) (pre-charge: 66')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)	98 (30)	98 (30)
Conn. Pipe Diameter Inch	Suc. 3/8 Dis. 1/4	Suc. 3/8 Dis. 1/4	Suc. 5/8" Dis. 3/8"	Suc. 5/8" Dis. 3/8"
Net Weight lbs. (kg)	18 (8) 71 (32)	18 (8) 71 (32)	31 (14) 135 (61)	31 (14) 135 (61)
Dimensions: Height Inch	11-1/16 21-1/4	11-1/16 21-1/4	12-5/8 32-3/4	12-5/8 32-3/4
mm	280 540	280 540	320 830	320 830
Width Inch	31-1/16 26	31-1/16 31	39-1/4 35-3/8	39-1/4 35-3/8
mm	790 660	790 790	998 900	998 900
Depth Inch	8 11-7/16	8 11-7/16	9 13	9 13
mm	203 290	203 290	228 330	228 330
Refrigerant	R410A	R410A	R410A	R410A
Indoor	ASU9RLF	ASU12RLF	ASU18RLF	ASU24RLF
Outdoor	AOU9RLF	AOU12RLF	AOU18LXFW	AOU24RLXFW

Note: Figures are based on 230 Volts.

Wall Mounted 30,000 BTU Systems

SYSTEM 30RLX



17.5 SEER

Function

This wall mounted heat pump provides both heating and cooling for year-round comfort. Ultra compact yet efficient, System 30RLX provides maximum comfort in 30% less space while saving you money. Additionally, System 30RLX provides low ambient operation rated down to 0°F right out of the box without modification.

Standard Features

- Wireless Remote Control
- Apple Catechin Filter
- Ion Deodorizing Filter
- Sleep Timer
- 24-Hour Timer
- Weekly Timer*
- Dry Mode
- Auto Louver: 4-way
- Auto Mode
- Minimum Heat Mode
- Economy Mode
- Quiet Mode (Indoor)
- Power Diffuser
- Auto Restart/Reset
- Auto Changeover
- 0°F Ambient Cooling
- Long Piping Length
- Cold Prevention
- Pump Down Operation
- 3rd Party Device Control**

* Available only with optional wired remote controller.
**Operation monitoring and On/Off control only.

Optional Wired Remote

- Weekly Timer
- Full Function Wired Remote
- Child Lock Capable



Easy Maintenance

Front panel is easily removed for cleaning.



Applications

Fujitsu ductless heat pumps can be used to solve various application-specific problems. Businesses and institutions such as schools, churches, nursing homes and hospitals, commercial office buildings, strip malls, motels and restaurants, apartments and condos, computer and telephone switching rooms, and even residences commonly use these systems. With more efficient zone control, "ductless mini-splits" are perfect for renovations, restorations, conversions, and add-ons.

30RLX Heat Pump	
Nominal Cooling BTU/h	30,000
Min.~Max. Cooling BTU/h	9,900~32,400
Nominal Heating BTU/h	32,000
Min.~Max. Heating BTU/h	8,000~37,500
HSPF BTU/hW	9.5
SEER BTU/hW	17.5
EER Clg/Htg	10.0
Clg. Operating Range °F(°C)	0~115 (-18~46)
Htg. Operating Range °F(°C)	0~75 (-18~24)
Moisture Removal Pt./h(l/h)	9.5 (4.5)
Voltage/Frequency/Phase	208-230/60/1
Recommended Fuse Size (A)	30
Air Circ. C.F.M. (m ³ /h): Hi	659 (1,120) Clg 677 (1,150) Htg
Medium	530 (900)
Low	435 (740)
Quiet	365 (620)
Noise Level dB(A): Hi	49/49 (Clg/Htg)
Medium	42/42 (Clg/Htg)
Low	37/37 (Clg/Htg)
Quiet	33/33 (Clg/Htg)
Outdoor Fan Speed RPM Clg/Htg	850/850
Outdoor Noise Level dB(A)	54/55 (Clg/Htg)
Current Rated/Max (A): Cooling	13.2/17.0
Heating	13.1/18.5
Power Use Rated/Max (kW): Cooling	3.0/3.87
Heating	2.99/4.22
Fan Speeds Stage	4 + Auto
Air Direction: Horizontal	Automatic
Vertical	Automatic
Air Filter	Washable
ENERGY STAR® Qualified	No
Connection Method	Flare
Combined Min. Lgth Ft (m)	16 (5)
Combined Max. Lgth Ft (m)	164 (50) (pre-charge: 66')
Max. Vertical Diff. Ft (m)	98 (30)
Conn. Pipe Diameter Inch	Suc. 5/8 Dis. 3/8
Net Weight lbs. (kg)	31 (14) 135 (61)
Dimensions: Height Inch	12-5/8 32-3/4
mm	320 830
Width Inch	39-1/4 35-3/8
mm	998 900
Depth Inch	9 13
mm	228 330
Refrigerant	R410A

Indoor ASU30RLX
Outdoor AOU30RLX

Note: Figures are based on 230 Volts.



Wall Mounted 18, 24, 30 and 36,000 BTU Cooling Systems

SYSTEMS 18CL, 24CL1, 30CLX1, 36CLX1

Up to 19.0 SEER



Function

Stylish, slim and elegant, these cooling-only wall mounted units are designed for single rooms. Indoor units have a clean, aesthetic design and are small but mighty and shorter in length than competing units, helping them blend into any room.

Standard Features

- Wireless Remote Control
- Apple Catechin Filter
- Ion Deodorizing Filter
- Sleep Timer
- 24-Hour Timer
- Weekly Timer*
- Dry Mode
- Auto Louver: Up/Down*
- Auto Louver: 4 Way^
- Auto Mode
- Quiet Mode
- Power Diffuser^
- Auto Restart/Reset
- Low Ambient Cooling
- Long Piping Length#
- Pump Down Operation#
- 3rd Party Device Control^



* Available only with optional wired remote controller.
 + Feature of 18CL only.
 ^ Feature of 24CL1, 30CLX1, 36CLX1 only. Operation monitoring and On/Off control only.
 # Feature of 30CLX1 and 36CLX1 only.

Optional Wired Remote

- Weekly Timer
- Full Function Wired Remote
- Child Lock Capable



UTY-RNBYU



	18CL	24CL1	30CLX1	36CLX1
	Cooling Only Cooling Only Cooling Only Cooling Only			
Nominal Cooling BTU/h	18,000	24,000	30,800	33,000
Min.~Max. Cooling BTU/h	5,500~19,000	3,100~25,000	9,900~32,400	9,900~34,100
SEER BTU/hW	19.0	17.5	16.5	15.5
EER Clg	10.4	10.0	9.5	8.5
Clg. Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Moisture Removal Pt./h(l/h)	5.9 (2.8)	6.3 (3.0)	9.7 (4.6)	10.1 (4.8)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	20	20	30	30
Air Circ. C.F.M. (m ³ /h): Hi	412 (700)	659 (1,120)	660 (1,100)	695 (1,180)
Medium	342 (581)	530 (900)	530 (900)	530 (900)
Low	271 (460)	436 (740)	435 (740)	435 (740)
Quiet	218 (370)	365 (620)	365 (620)	365 (620)
Noise Level dB(A): Hi	44	48	49	50
Medium	38	42	42	42
Low	32	37	37	37
Quiet	25	33	33	33
Outdoor Fan Speed RPM Clg	860	1,100	2,119	2,119
Outdoor Noise Level dB(A)	50	56	54	54
Current Rated/Max (A): Cooling	7.7/9.0	10.5/11.5	14.2/17.0	17.0/18.0
Power Use Rated/Max (kW): Cooling	1.73/2.0	2.4/2.5	3.24/3.87	3.88/4.10
Fan Speeds Stage	4 + Auto	4 + Auto	4 + Auto	4 + Auto
Air Direction: Horizontal	Manual	Automatic	Automatic	Automatic
Vertical	Automatic	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable	Washable
Connection Method	Flare	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	9 (2.7)	9 (2.7)	16 (5)	16 (5)
Combined Max. Lgth Ft (m)	66 (20)	98 (30)	164 (50)	164 (50)
	(pre-charge: 49')	(pre-charge: 49')	(pre-charge: 66')	(pre-charge: 66')
Max. Vertical Diff. Ft (m)	49 (15)	66 (20)	98 (30)	98 (30)
Conn. Pipe Diameter Inch	Suc. 1/2 Dis. 1/4	Suc. 5/8 Dis. 1/4	Suc. 5/8 Dis. 3/8	Suc. 5/8 Dis. 3/8
Net Weight lbs. (kg)	20 (9)	88 (40)	31 (14)	88 (40)
	31 (14)	31 (14)	135(61)	31 (14)
	135(61)	31 (14)	31 (14)	135(61)
Dimensions: Height Inch	10-13/16	22-3/4	12-5/8	24-7/16
	12-5/8	12-5/8	32-3/4	12-5/8
	32-3/4	12-5/8	32-3/4	32-3/4
mm	275	578	320	620
	320	320	830	320
	830	320	320	830
Width Inch	31-1/8	31-1/8	39-1/4	31-1/8
	39-1/4	39-1/4	35-3/8	39-1/4
	35-3/8	39-1/4	35-3/8	35-3/8
mm	790	790	998	790
	998	998	900	998
	900	998	900	900
Depth Inch	8-7/16	11-13/16	9	11-3/4
	9	9	13	9
	13	9	13	13
mm	215	300	228	298
	228	228	330	228
	228	330	228	330
Refrigerant	R410A	R410A	R410A	R410A
Indoor ASU18CL				
Outdoor AOU18CL				
Indoor ASU24CL1				
Outdoor AOU24CL1				
Indoor ASU30CLX1				
Outdoor AOU30CLX1				
Indoor ASU36CLX1				
Outdoor AOU36CLX1				

Note: Figures are based on 230 Volts.

Ceiling and Universal Floor/Ceiling Mounted Systems

SYSTEMS 18RULX, 24RULX, 36RSLX



Up to 16 SEER

Function

The 18RULX and the 24RULX are universal mount. They can mount low on the wall or transverse mount them on the ceiling. The 36RSLX can only be mounted on the ceiling, can take in fresh air and can throw air farther.

Standard Features


- Wireless Remote Control
- Sleep Timer
- 24 Hour Timer
- Weekly Timer*
- Dry Mode
- Auto Louver: 4 Way
- Auto Mode
- Auto Restart/Reset
- Auto Changeover
- 0°F Ambient Cooling
- Long Piping Length
- Cold Prevention
- Energy Saver*
- Remote Temp. Sensor*
- Daisy Chain
- Pump Down Operation
- High Ceiling Mode
- Fresh Air Intake[^]

*Available only with optional wired remote controller.

[^]Fresh air knockout available. Fresh air fan and ductwork field supplied. See Design and Technical Manual for details

Optional Accessories

- Wired Remote Control UTY-RNBYU*
 - Weekly Timer
 - Full Function Wired Remote
 - Child Lock Capable
- Condensate Pump UTR-DPB24T
 - OEM design plug and play
 - Rated for 11.8" of vertical lift.



Applications

The universal mount 18RULX and 24RULX are ideal for a house of worship to mount beneath stained glass windows. Lower in height than the pews, they do not disturb the aesthetics of the space. With long piping lengths of 165' the outdoor units can also be placed remotely out of sight. Another popular application for this model is in hallways where wall space is limited. The 36RSLX is popular where fresh air intake and high capacity is required like a restaurant or bar. They are also often suspended from threaded rod and used in multiple to condition large warehouse spaces.



	18RULX Heat Pump	24RULX Heat Pump	36RSLX Heat Pump
Nominal Cooling BTU/h	17,800	22,200	34,100
Min.~Max. Cooling BTU/h	5,000~21,600	5,000~27,300	8,500~36,000
Nominal Heating BTU/h	21,500	24,000	36,500
Low Heating 17°F BTU/h	13,000	15,000	23,400
Min.~Max. Heating BTU/h	5,000~25,600	5,000~29,000	9,200~42,700
HSPF BTU/hW	8.5	8.5	8.5
SEER BTU/hW	16.0	15.0	14.0
EER Clg/Htg	10.9/9.6	9.9/10.2	8.1/10.4
Clg. Operating Range °F(°C)	0~115 (-18~46)	0~115 (-18~46)	0~115 (-18~46)
Htg. Operating Range °F(°C)	14~75 (-10~24)	14~75 (-10~24)	14~75 (-10~24)
Moisture Removal Pt./h(l/h)	5.3 (2.5)	7.4 (3.5)	7.4 (3.5)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	20	20	30
Air Circ. C.F.M. (m ³ /h): Hi	459 (780)	518 (880)	1089 (1850)
Medium	383 (650)	436 (740)	977 (1660)
Low	324 (550)	371 (630)	842 (1430)
Noise Level dB(A): Hi	43/43 (Clg/Htg)	47/47 (Clg/Htg)	48/48 (Clg/Htg)
Medium	39/39 (Clg/Htg)	43/43 (Clg/Htg)	45/43 (Clg/Htg)
Low	35/35 (Clg/Htg)	38/38 (Clg/Htg)	41/39 (Clg/Htg)
Outdoor Fan Speed RPM	780/780	850/900	850/900
Outdoor Noise Level dB(A)	51/53	53/55	54/55
Current Rated/Max (A): Cooling	7.1/12.5	9.8/12.5	18.3/18.8
Heating	9.8/12.5	10.2/12.5	15.3/18.8
Power Use Rated/Max (kw): Cooling	1.63/2.88	2.25/2.88	4.22/4.35
Heating	2.25/2.88	2.35/2.88	3.50/4.35
Fan Speeds Stage	3 + Auto	3 + Auto	3 + Auto
Air Direction: Horizontal	Automatic	Automatic	Automatic
Vertical	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable
Front Grille	Permanent	Permanent	Permanent
Connection Method	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	16 (5)	16 (5)	16 (5)
Combined Max. Lgth Ft (m)	165 (50) (pre-charge: 49')	165 (50) (pre-charge: 49')	165 (50) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	66 (20)	66 (20)	98 (30)
Conn. Pipe Diameter Inch	Suc. 1/2 Dis. 1/4	Suc. 5/8 Dis. 3/8	Suc. 5/8 Dis. 3/8
Net Weight lbs. (kg)	62 (28)	141 (64)	62 (28)
Dimensions: Height Inch	7-7/8	32-3/4	7-7/8
mm	199	830	199
Width Inch	39-1/8	35-1/2	39-1/8
mm	990	900	990
Depth Inch	25-7/8	13	25-7/8
mm	655	330	655
Refrigerant	R410A	R410A	R410A
Indoor ABU18RULX	Outdoor AOU18RULX	Indoor ABU24RULX	Outdoor AOU24RULX
Indoor ABU36RSLX	Outdoor AOU36RSLX		

Note: Figures are based on 230 Volts.

Compact Duct Single Zone 9, 12 and 18,000 BTU Systems

SYSTEMS 9RLFCD, 12RLFCD, 18RLFCD



Federal Tax Credit Qualified
See Page 9 for details
Systems 9RLFCD and 12RLFCD only.



Up to 21.5 SEER



Function




Compact ducts provide comfort cooling or heating for small room applications. Features include high efficiency

up to 21.5 SEER, heating at low temperatures down to -5°F, compact design, quiet operation, a standard wired remote control, and the ability to bring in fresh air.

High Performance Heating

Heating capacity at low outdoor temperatures is achieved by adopting a large heat exchanger and a high capacity compressor. Systems operate down to -5°F.



Standard Features

- Wired Remote Control
- Auto Changeover
- Weekly Timer
- Low Ambient Cooling
- Dry Mode
- Cold Prevention
- Auto Mode
- Daisy Chain
- Economy Mode
- Built-In Condensate Pump
- Minimum Heat Auto
- 3rd Party Device Control[^]
- Auto Restart/Reset

^{*}Available only with optional wireless remote controller.
[^]Operation monitoring and On/Off control only.

Applications

Long maximum combined piping length of 66' and 49' in height allow for versatile installations. Flexible installation, either horizontal or vertical, and low height enables compact soffit or cabinet installation. These features make compact duct systems ideal for commercial applications such as offices, restaurants, convenience stores, motels, dorms, in retrofit and new construction.



Multi-Tenant Dwellings



Hotels / Motels



Dorms

Optional Accessories

- Backlit Wired Remote Control UTY-RVNUM *Displays room temp.*
- Wireless Remote and Receiver Unit UTY-LRHUM



UTY-RVNUM

Field Supplied Filters Used With Compact Duct Units

Although Compact Duct units come with factory filters, when return ductwork is used field supplied filters are more practical to use. They can be installed at the unit or for more convenient servicing, in filter grilles. See the guidelines to the right to determine filter sizes.

The chart includes CFM, external static pressure capability and a typical filter size for each model. Filters are sized to keep velocities and static pressure loss low. This will insure sufficient static pressure is available for ductwork, fittings and supply and return grilles.

Alternative filter sizes with equivalent face areas can be used. After deducting filter loss, available static pressure values are shown.




A fiberglass filter is shown in blue to the left. A MERV pleated filter is shown in white.


	ARU 9RLF	ARU 12RLF	ARU 18RLF
CFM	353	353	547
Typical Filter Size	12 x 20	12 x 20	14 x 25
Velocity, FPM	212	212	225
Unit External SP, in. W.C.	0.36	0.36	0.36
1" Fiberglass Filter			
SP Loss, in. W.C.	0.04	0.04	0.04
Available Static Pressure	0.32	0.32	0.32
1" MERV 8 Pleated Filter			
SP Loss, in. W.C.	0.12	0.12	0.14
Available Static Pressure	0.24	0.24	0.22
2" MERV 8 Pleated Filter			
SP Loss, in. W.C.	0.07	0.07	0.08
Available Static Pressure	0.29	0.29	0.28

Compact Duct

Built-in drain pump allows for installation of compact duct unit in smaller spaces than traditional units.




Return Air-intake Choices



Flexible Installation

Horizontal or vertical.



*Internal drain pump will not operate when the unit is mounted in a vertical configuration.



	9RLFCD Heat Pump	12RLFCD Heat Pump	18RLFCD Heat Pump
Nominal Cooling BTU/h	9,000	12,000	18,000
Min~Max Cooling BTU/h	3,100~12,000	3,100~13,600	3,100~20,100
Nominal Heating BTU/h	12,000	16,000	21,600
Min~Max Heating BTU/h	3,100~18,000	3,100~19,400	3,100~25,600
HSPF	12.2	11.5	11.3
SEER	21.5	20.0	19.7
EER Clg/Htg	14.5/14.1	12.8/12.3	12.0/12.9
Cooling Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Heating Operating Range °F(°C)	-5~75 (-21~24)	-5~75 (-21~24)	-5~75 (-21~24)
Moisture Removal Pt./h(l/h)	1.5 (.07)	2.7 (1.3)	4.2 (2.0)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	15	15	20
Static Pressure In. W. C.	0 ~ 0.36	0 ~ 0.36	0 ~ 0.36
Air Circ. C.F.M. (m ³ /h) Clg/Htg: Hi	353 (600)	383 (650)	554 (940)
Medium	324 (550)	353 (600)	518 (880)
Low	294 (500)	324 (550)	483 (820)
Quiet	265 (450)	283 (480)	442 (750)
Noise Level dB(A) (Clg/Htg): Hi	28/28	29/29	32/32
Medium	27/26	28/28	30/30
Low	26/25	27/27	29/29
Quiet	25/24	26/24	27/27
Outdoor Fan Speed RPM Clg/Htg	590/720	870/780	870/1,000
Outdoor Noise Level Clg/Htg	48/49	49/50	54/55
Running Current Rated (A) Clg/Htg	3.0/3.9	4.4/6.0	6.6/7.3
Power Use Rated/Max (kW): Cooling	0.62/1.40	0.94/1.45	1.50/2.15
Heating	0.85/1.80	1.30/2.00	1.67/2.60
Fan Speeds Stage	4 + Auto	4 + Auto	4 + Auto
Air Filter	Washable	Washable	Washable
Connection Method	Flare	Flare	Flare
Combined Min. Length Ft (m)	9 (2.7)	9 (2.7)	9 (2.7)
Combined Max. Length Ft (m)	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)	49 (15)
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4
Indoor Unit Net Weight lbs. (kg)	41 (19)	41 (19)	50 (23)
Outdoor Unit Net Weight lbs. (kg)	84 (38)	84 (38)	86 (39)
Indoor Unit Dimensions: Height Inch (mm)	7-25/32 (198)	7-25/32 (198)	7-25/32 (198)
Width Inch (mm)	27-9/16 (700)	27-9/16 (700)	35-7/16 (900)
Depth Inch (mm)	24-13/32 (620)	24-13/32 (620)	24-13/32 (620)
Supply Duct Flange Dimensions: Height Inch (mm)	5-15/16 (151)	5-15/16 (151)	5-15/16 (151)
Width Inch (mm)	25-19/32 (650)	25-19/32 (650)	33-15/32 (850)
Depth Inch (mm)	3/4 (19)	3/4 (19)	3/4 (19)
Return Duct Flange Dimensions: Height Inch (mm)	6-27/32 (174)	6-27/32 (174)	6-27/32 (174)
Width Inch (mm)	22-19/32 (574)	22-19/32 (574)	30-15/32 (774)
Depth Inch (mm)	3/4 (19) (Flat)	3/4 (19) (Flat)	3/4 (19) (Flat)
Outdoor Unit Dimensions: Height Inch (mm)	24-1/2 (620)	24-1/2 (620)	24-1/2 (620)
Width Inch (mm)	31-3/32 (790)	31-3/32 (790)	31-3/32 (790)
Depth Inch (mm)	11-11/32 (290)	11-11/32 (290)	11-11/32 (290)
Refrigerant	R410A	R410A	R410A

Note: Figures are based on 230 Volts.



Systems 9RLFCD, 12RLFCD

Compact Cassette Single Zone 9, 12 and 18,000 BTU

SYSTEMS 9RLFCC, 12RLFCC, 18RLFCC



Federal Tax Credit Qualified
See Page 9 for details
Systems 9RLFCC and 12RLFCC only.



Up to 24.0 SEER

Function




Compact cassettes provide comfort cooling or heating for small room applications.

Features include high efficiency up to 24.0 SEER, heating at low temperatures down to -5°F, compact design, quiet operation, a standard wired remote control, and the ability to bring in fresh air through the optional Fresh Air Kit.

High Performance Heating

Heating capacity at low outdoor temperatures is achieved by adopting a large heat exchanger and a high capacity compressor. Systems operate down to -5°F.



Standard Features

- Wired Remote Control
- Weekly Timer
- Dry Mode
- Auto Louver: Up/Down
- Auto Mode
- Minimum Heat*
- Economy Mode
- Auto Restart/Reset
- Auto Changeover
- Low Ambient Cooling
- Cold Prevention
- Daisy Chain
- High Ceiling Mode
- Condensate Pump
- Fresh Air Intake**
- 3rd Party Device Control^



Fresh Air Kit**
UTZ-VXAA
Mixes room air then passes through the heat exchanger.

Applications

Long maximum combined piping length of 66' and 49' in height allow for versatile installations. 4-way airflow, concealed flush mount design and the ability to operate in limited space above the drop ceiling, makes these systems ideal for commercial applications such as offices, restaurants, convenience stores, motels, dorms, in retrofit and new construction.



Multi-Tenant Dwellings



Hotels / Motels



Dorms



Optional Accessories

- Backlit Wired Remote Control UTY-RVNUM *Displays room temp.*
- Wireless remote UTY-LNHUM



UTY-RVNUM


* Available only with optional wireless remote control.

**Requires Fujitsu's Optional Fresh Air Kit part #UTZ-VXAA. Allows for a 4-inch flex duct connection. Requires a field supplied duct booster fan capable of 60 CFM at .2"W.C. or 90 CFM at .4"W.C. For fan static pressure requirements, see installation manual. Add hood, filter and duct losses for fan total static pressure requirements. Will add 4" to the height of the indoor unit.

^ Operation monitoring and On/Off control only.

Easy Installation


Fits into a standard ceiling tile*.



*Dimensions of outer grille are 27-9/16" x 27-9/16" and may overlap adjacent tiles.


2-Stage Turbo Fan

Air distribution is evenly spread across the heat exchanger by the 2 stage turbo fan which produces two separate airflow streams.



Quiet Operation

Optimization of wing form (laminar wing design) and number of wings (7 blades) enables as low as 27 dB.



	9RLFCC Heat Pump	12RLFCC Heat Pump	18RLFCC Heat Pump
Nominal Cooling BTU/h	9,000	12,000	18,000
Min~Max Cooling BTU/h	3,100~12,000	3,100~13,600	3,100~20,100
Nominal Heating BTU/h	12,000	16,000	21,600
Min~Max Heating BTU/h	3,100~18,000	3,100~19,400	3,100~25,600
HSPF	13.0	12.2	11.5
SEER	24.0	21.9	20.1
EER Clg/Htg	14.5/13.5	12.8/11.1	11.2/12.3
Cooling Operating Range °F(°C)	14~115 (-10~46)	14~115 (-10~46)	14~115 (-10~46)
Heating Operating Range °F(°C)	-5~75 (-21~24)	-5~75 (-21~24)	-5~75 (-21~24)
Moisture Removal Pt./h/h	1.3 (.06)	2.5 (1.2)	4.6 (2.2)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	15	15	20
Air Circ. C.F.M. (m ³ /h): Hi	318 (540)	359 (610)	400 (680)
Medium	288 (490)	312 (530)	341 (580)
Low	259 (440)	277 (470)	288 (490)
Quiet	230 (390)	241 (410)	241 (410)
Noise Level dB(A) Clg/Htg: Hi	33/34	37/37	40/44
Medium	32/32	33/33	36/40
Low	29/29	31/31	32/36
Quiet	28/27	28/28	28/30
Outdoor Fan Speed RPM Clg/Htg	590/720	870/780	1,050/1,000
Outdoor Noise Level Clg/Htg	48/49	49/50	54/55
Running Current Rated (A): Cooling	3.0	4.4	7.1
Heating	4.1	6.7	7.7
Power Use Rated/Max (kW): Clg	0.62/1.40	0.94/1.45	1.61/2.15
Heating	0.89/1.80	1.44/2.00	1.76/2.60
Fan Speeds Stage	4+auto	4+auto	4+auto
Air Direction: Vertical	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable
Front Grille	UTG-CCGF*	UTG-CCGF*	UTG-CCGF*
Connection Method	Flare	Flare	Flare
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4
Combined Min. Length Ft (m)	9 (2.7)	9 (2.7)	9 (2.7)
Combined Max. Length Ft (m)	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')	66 (20) (pre-charge: 49')
Max. Vertical Diff. Ft (m)	49 (15)	49 (15)	49 (15)
Indoor Unit Net Weight lbs. (kg)	33 (15)	33 (15)	33 (15)
Outdoor Unit Net Weight lbs. (kg)	84 (38)	84 (38)	86 (39)
Indoor Unit Dim: Height Inch (mm)	9-11/16 (245)	9-11/16 (245)	9-11/16 (245)
Width Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Depth Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Grille Dim: Height Inch (mm)	1-15/16 (49)	1-15/16 (49)	1-15/16 (49)
Width Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Depth Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Outdoor Unit Dim: Height Inch (mm)	24-1/2 (620)	24-1/2 (620)	24-1/2 (620)
Width Inch (mm)	31-3/32 (790)	31-3/32 (790)	31-3/32 (790)
Depth Inch (mm)	11-11/32 (290)	11-11/32 (290)	11-11/32 (290)
Refrigerant	R410A	R410A	R410A

* Compact Cassette Grille UTG-CCGF sold separately. Must order one with each compact cassette.

Note: Figures are based on 230 Volts.



Systems 9RLFCC, 12RLFCC

Ceiling Cassette Systems

SYSTEMS 18RCLX, 24RCLX, 36RCLX, 42RCLX



Up to 16.0 SEER

Function

Up to 16-SEER, these models provide up to 30% increase in efficiency over 13-SEER models. These models offer the ability to send up to 38% of their capacity through two branch ducts to adjacent rooms. Slender fit feature now offered on all models decreases space required above the ceiling increasing application opportunities.

Standard Features



Weekly Timer	Cold Prevention
Dry Mode	Slender Fit
Auto Louver: Up/ Down	Remote Temp. Sensor
Auto Mode	Daisy Chain
Energy Saver	Pump Down Operation
Auto Restart/Reset	High Ceiling Mode
Auto Changeover	Branch Duct Capable
0°F Ambient Cooling	Built-in Condensate Pump
Long Piping Length	Fresh Air Intake*

Applications

Four-way airflow, concealed flush mount design and the ability to operate in high ceiling rooms makes these systems ideal for commercial applications such as offices, conference rooms, restaurants, night clubs and bars in retrofit and new construction. Long maximum combined piping lengths of 165 to 230 feet with 60 to 98 feet of height, depending on model, allow the outdoor unit to be remotely located up to 7 stories away and far from indoor unit. The ceiling cassettes are also used in new construction condominiums and homes taking advantage of their branch duct capability to feed adjacent rooms. These heat pumps provide up to 30% additional available heat when compared to conventional models.

Standard Wired Remote

- Weekly timer
- Set on-off time twice a day
- Set different on-off time by day
- Set time in 5 minute intervals
- Control up to 16 indoor units
- Child lock capable
- Remote temperature sensor



Slender Fit

Cassette body can be moved downward into the room 1-3/8" to accommodate limited ceiling space.

*Fresh air knockout available. Fresh air fan and ductwork field supplied. See design and technical manual for details. Fujitsu fresh air intake kit available part #KHRS940-25.



Fujitsu provides knock-outs on all ceiling cassettes where contractors can:

- Install optional field supplied branch ducts on up to two sides to supply up to 18% capacity per side to adjoining spaces up to 16 feet away. See Design and Technical Manual for details.
- Allows fresh air to be brought into the indoor unit using fresh air knockout.



	18RCLX Heat Pump	24RCLX Heat Pump	36RCLX Heat Pump	42RCLX Heat Pump
Nominal Cooling BTU/h	17,800	22,200	34,100	42,700
Min.~Max. Cooling BTU/h	5,000~21,500	5,000~27,300	8,500~36,000	13,700~45,000
Nominal Heating BTU/h	21,000	24,200	36,000	45,200
Low Temp. Heating 17°F BTU/h	11,300	14,600	23,000	28,200
Min.~Max. Heating BTU/h	5,000~25,600	5,000~29,000	9,200~42,700	14,300~54,600
HSPF BTU/hW	8.5	8.5	8.5	8.5
SEER BTU/hW	16.0	15.0	14.0	15.0
EER Clg/Htg	11.1 / 10.2	10.6 / 10.2	8.1 / 9.7	9.2 / 10.5
Clg. Operating Range °F(°C)	0~115 (-18~46)	0~115 (-18~46)	0~115 (-18~46)	0~115 (-18~46)
Htg. Operating Range °F(°C)	14~75 (-10~24)	14~75 (-10~24)	14~75 (-10~24)	0~75 (-18~24)
Moisture Removal Pt./h(l/h)	5.3 (2.5)	6.4 (3.0)	8.5 (4.0)	11.6 (5.5)
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Recommended Fuse Size (A)	20	20	30	30
Air Circ. C.F.M. (m³/h): Hi	559 (950)	618 (1,050)	942 (1,600)	1,000 (1,700)
Medium	477 (810)	536 (910)	824 (1,400)	854 (1,450)
Low	394 (670)	436 (740)	677 (1,150)	736 (1,250)
Noise Level dB(A): Hi	42/40 (Clg/Htg)	45/43 (Clg/Htg)	48/48 (Clg/Htg)	50/50 (Clg/Htg)
Medium	39/38 (Clg/Htg)	43/39 (Clg/Htg)	45/45 (Clg/Htg)	48/48 (Clg/Htg)
Low	36/36 (Clg/Htg)	38/35 (Clg/Htg)	41/41 (Clg/Htg)	44/44 (Clg/Htg)
Outdoor Fan Speed RPM	780/780	850/900	850/900	850/750
Outdoor Noise Level dB(A)	51/53 (Clg/Htg)	53/55 (Clg/Htg)	54/55 (Clg/Htg)	55/56 (Clg/Htg)
Current Rated/Max (A): Cooling	7.0/12.5	9.2/12.5	18.3/18.8	20.3/21.7
Heating	8.9/12.5	10.4/12.5	16.1/18.8	18.8/21.7
Power Use Rated/Max (kw): Clg	1.61/2.88	2.10/2.88	4.22/4.35	4.66/4.99
Heating	2.05/2.88	2.37/2.88	3.70/4.35	4.31/4.99
Fan Speeds Stage	3 + Auto	3 + Auto	3 + Auto	3 + Auto
Air Direction: Horizontal	-	-	-	-
Vertical	Automatic	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable	Washable
Front Grille	Removable	Removable	Removable	Removable
Connection Method	Flare	Flare	Flare	Flare
Combined Min. Lgth Ft (m)	16 (5)	16 (5)	16 (5)	16 (5)
Combined Max. Lgth Ft (m)	165 (50) Each (pre-charge: 49')	165 (50) Each (pre-charge: 49')	165 (50) Each (pre-charge: 49')	165 (50) Each (pre-charge: 66')
Max. Vertical Diff. Ft (m)	65 (20)	65 (20)	98 (30)	98 (30)
Conn. Pipe Diameter Inch	Suc. 1/2 Dis. 1/4	Suc. 5/8 Dis. 3/8	Suc. 5/8 Dis. 3/8	Suc. 5/8 Dis. 3/8
Net Weight lbs. (kg)	75 (34) 141 (64)	75 (34) 141 (64)	82 (37) 141 (64)	88 (40) 231 (105)
Dimensions: Height Inch	9-3/4 32-3/4	9-3/4 32-3/4	11-5/8 32-3/4	11-5/8 50-7/8
mm	246 830	246 830	296 830	296 1290
Width Inch	32-3/4 35-1/2	32-3/4 35-1/2	32-3/4 35-1/2	32-3/4 35-1/2
mm	830 900	830 900	830 900	830 900
Depth Inch	32-3/4 13	32-3/4 13	32-3/4 13	32-3/4 13
mm	830 330	830 330	830 330	830 330
Refrigerant	R410A	R410A	R410A	R410A
	Indoor AUU18RCLX Outdoor AOU18RLX	Indoor AUU24RCLX Outdoor AOU24RLX	Indoor AUU36RCLX Outdoor AOU36RLX	Indoor AUU42RCLX Outdoor AOU42RLX

Note: Figures are based on 230 Volts.

MULTI ZONE MINI-SPLIT SYSTEMS

*Revolutionary Halcyon
HFI systems are changing
the way we define comfort*

- Operate as few as one indoor unit or all indoor units
- Choose from 3 indoor unit styles - wall mount, compact duct or cassette, including Designer Series RLS2 wall mount units
- Four combinations are ENERGY STAR® Qualified
- Create over 9,700 combinations based on indoor type and BTU



- Connect 2 to 4 indoor units, depending on model
- Connect 14,000 to 39,000 BTU
- No branch boxes or separation tubes required



- Connect 2 to 8 indoor units
- 80 to 130% connectable capacity
- Connect 39,000 to 62,000 BTU
- Branch boxes and separation tubes required



Multi-Zone Outdoor Units 18, 24 and 36,000 BTUs

AOU18RLXFZ, AOU24RLXFZ, AOU36RLXFZ



Part of the Halcyon Hybrid Flex Inverter (HFI) Line

As part of the Halcyon HFI line of equipment, select indoor units are compatible with other HFI outdoor units, meaning mix and match capabilities with fewer components.

Connectable Capacity

This function allows you to connect indoor units that can exceed outdoor unit capacity (See sizing guide on page 43 for details). However, if you connect indoor units that exceed 100% of the outdoor unit's capacity there are limitations.

If all indoor units are cooling or heating at the same time, the system will limit their capacity so that their total matches the outdoor unit's capacity. When a zone meets a desired set temperature it requires less capacity. The unused capacity is then distributed to the remaining indoor units, increasing their capacity.

For Example

The load on a 3-bedroom home with a living room and kitchen downstairs and 3 bedrooms upstairs is 39,000 BTUs (21,000 BTU downstairs and 18,000 BTU upstairs). However the family isn't upstairs and downstairs at the same time, therefore not all units will be running simultaneously allowing 100% heating or cooling to occupied spaces. This can be achieved by our AOU36RLXFZ outdoor unit.

Flex Zone Outdoor Unit 48,000 BTUs

AOU48RLXFZ1



Halcyon HFI Flex Zone system's zoning capability allows you to set each indoor unit to a different temperature - that means you can set up to 8 different temperatures as needed! This system provides individual temperature control throughout your home or business so each room, zone or floor will be the temperature you set! An optional Central Remote Control is available which can control up to all 8 indoor units from one keypad. Additionally, you can set timers - 24-hour timer and sleep timer - for your convenience.

130% Connectable Capacity

The HFI system is rated at 48,000 BTUs but you can connect up to 130%, or 62,000 BTUs of rated indoor unit capacity to the AOU48RLXFZ1. Connectable capacity allows you to connect indoor units that can exceed outdoor unit capacity (See sizing guide on page 44 for details). However, if you connect indoor units that exceed 100% of the outdoor unit's capacity there are limitations.

If all indoor units are cooling or heating at the same time, the system will limit their capacity so that their total matches the outdoor unit's capacity. When a zone meets a desired set temperature it requires less capacity. The unused capacity is then distributed to the remaining indoor units, increasing their capacity.

For Example

The load on a small 2-story office building with a business downstairs and worker apartments upstairs is 62,000 BTUs (38,000 BTUs downstairs and 24,000 BTUs upstairs) but the workers aren't upstairs and downstairs at the same time, therefore not all units will be running simultaneously allowing 100% heating or cooling to occupied spaces.



Mix and Match Flexibility



Wall Mounts

The ability to create the right combinations, the right quantity (up to 8-zones), the right style indoor units, and the right capacity.



ASU7, 9, 12RLF



ASU9, 12RLS2



ASU15RLS2



ASU18RLF



ASU24RLF

Compact Ducts

It's the RIGHT choice for your home or business.



ARU9, 12RLF




ARU18RLF



ARU24RLF

Separation Tubes, Branch Boxes

Compact Cassettes



UTP-SX248A



UTP-PU03A, UTP-PU03B



AAU9, 12RLF



AAU18RLF



Wall Mounted 7, 9, 12, 18 and 24,000 BTUs



ASU7RLF, ASU9RLF, ASU9RLS2, ASU12RLF, ASU12RLS2, ASU15RLS2, ASU18RLF, ASU24RLF



ASU7, 9, 12RLF



ASU18, 24RLF



ASU9, 12, 15RLS2[^]

Designer Series

	ASU7RLF Heat Pump	ASU9RLF Heat Pump	ASU12RLF Heat Pump	ASU18RLF Heat Pump	ASU24RLF Heat Pump	ASU9RLS2 Heat Pump [^]	ASU12RLS2 Heat Pump [^]	ASU15RLS2 Heat Pump [^]
Nominal Cooling BTU/h*	7,000	9,000	12,000	18,000	24,000	9,000	12,000	14,000
Nominal Heating BTU/h*	8,100	10,200	13,500	20,000	27,000	10,200	13,500	16,300
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Air Circ. C.F.M. (m ³ /h): Hi	Clg 330 (560) Htg 330 (560)	Clg 353 (600) Htg 353 (600)	Clg 388 (660) Htg 388 (660)	Clg 542 (920) Htg 542 (920)	Clg 659 (1,120) Htg 647 (1,100)	Clg 353 (600) Htg 353 (600)	Clg 388 (660) Htg 388 (660)	Clg 418 (710) Htg 418 (710)
	Medium	Clg 294 (500) Htg 294 (500)	Clg 306 (520) Htg 306 (520)	Clg 330 (560) Htg 330 (560)	Clg 436 (740) Htg 436 (740)	Clg 530 (900) Htg 530 (900)	Clg 324 (550) Htg 324 (550)	Clg 353 (600) Htg 353 (600)
Low	Clg 253 (430) Htg 253 (430)	Clg 253 (430) Htg 253 (430)	Clg 265 (450) Htg 277 (470)	Clg 365 (620) Htg 365 (620)	Clg 436 (740) Htg 436 (740)	Clg 277 (470) Htg 277 (470)	Clg 312 (530) Htg 312 (530)	Clg 336 (570) Htg 347 (590)
	Quiet	Clg 200 (340) Htg 206 (350)	Clg 200 (340) Htg 206 (350)	Clg 200 (340) Htg 206 (350)	Clg 324 (550) Htg 324 (550)	Clg 365 (620) Htg 365 (620)	Clg 194 (330) Htg 194 (330)	Clg 194 (330) Htg 194 (330)
Noise Level dB(A) (Clg/Htg): Hi	36/36	37/37	40/40	43/44	49/48	36/36	37/37	41/41
	Medium	32/32	33/33	36/36	37/37	32/32	34/34	36/36
	Low	29/29	29/29	30/31	33/33	28/28	31/31	33/34
	Quiet	25/25	25/25	25/25	31/31	33/33	21/21	25/27
Running Current Rated (A): Cooling	0.13	0.15	0.19	0.32	0.53	0.14	0.17	0.20
	Heating	0.13	0.15	0.19	0.32	0.53	0.14	0.17
Power Use Rated (w): Clg	15	17	22	41	69	16	19	23
	Htg	15	17	22	41	69	16	23
Fan Speeds Stage	4+auto	4+auto	4+auto	4+auto	4+auto	4+auto	4+auto	4+auto
Air Direction: Horizontal	Manual	Manual	Manual	Auto	Auto	Manual	Manual	Manual
	Vertical	Auto	Auto	Auto	Auto	Auto	Auto	Auto
Primary Air Filter	Washable	Washable	Washable	Washable	Washable	Washable	Washable	Washable
Ion Deodorizing Filter	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable
Apple-Catechin Filter	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable	Disposable
Connection Method	Flare	Flare	Flare	Flare	Flare	Flare	Flare	Flare
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4	suc 5/8 dis 1/4	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4
Net Weight lbs. (kg)	18 (8)	18 (8)	18 (8)	31 (14)	31 (14)	21 (9.5)	21 (9.5)	21 (9.5)
Dims: Height Inch (mm)	11-1/16 (280)	11-1/16 (280)	11-1/16 (280)	12-5/8 (320)	12-5/8 (320)	11-1/8 (282) 13-1/4* (337*)	11-1/8 (282) 13-1/4* (337*)	11-1/8 (282) 13-1/4* (337*)
	Width Inch (mm)	31-1/16 (790)	31-1/16 (790)	31-1/16 (790)	39-1/4 (998)	39-1/4 (998)	34-1/4 (870)	34-1/4 (870)
Depth Inch (mm)	8 (203)	8 (203)	8 (203)	9 (228)	9 (228)	7-1/4 (185)	7-1/4 (185)	7-1/4 (185)
Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A

[^]Not compatible with outdoor unit AOU48RLXFZ. *Height when front panel is open.

Standard Features

- Wireless Remote Control*
- Sleep Timer
- 24-Hour Timer
- Dry Mode
- Auto Louver: 4-Way**
- Auto Mode
- Minimum Heat Mode
- Auto Restart/Reset
- Power Diffuser**

Built In Filtration



Long-life Ion Deodorization Filter
The filter deodorizes by powerfully decomposing absorbed odors using the oxidizing and reducing effects of ions generated by the ultra-fine-particle ceramic.

+ The filter can be used for approximately 3 years if it is washed with water when dirty to restore its surface action.



Apple-Catechin Filter

Dust, mold spores and micro-organisms are absorbed onto the filter by static electricity and growth is inhibited and deactivated. Filter last 3-12 months.

* Features vary by model and therefore standard wireless remote controls should be used with the models they are associated with.

**Feature of models ASU18, 24RLF only.



Compact Duct 9, 12, 18 and 24,000 BTUs



ARU9RLF, ARU12RLF, ARU18RLF, ARU24RLF



ARU9, 12RLF



ARU18RLF



ARU24RLF

Compact Duct

Built-in drain pump allows for installation of compact duct unit in smaller spaces than traditional units.

Traditional



Compact Duct



Return Air-intake Choices




Standard Features

- Wired Remote Control
- Dry Mode
- Weekly Timer
- Auto Mode
- Quiet Mode
- Auto Restart/Reset
- Condensate Pump
- Fresh Air Intake

Flexible Installation

Horizontal or vertical*.



*Internal drain pump will not operate when the unit is mounted in a vertical configuration.



	ARU9RLF Heat Pump	ARU12RLF Heat Pump	ARU18RLF Heat Pump	ARU24RLF Heat Pump
Nominal Cooling BTU/h	9,000	12,000	18,000	24,000
Nominal Heating BTU/h	10,200	13,500	20,000	27,000
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Static Pressure In. W. C.	0 ~ 0.36	0 ~ 0.36	0 ~ 0.36	0 ~ 0.20
Air Circ. C.F.M. (m ³ /h) Clg/Htg: Hi	353 (600)	383 (650)	554 (940)	783 (1,330)
Medium	324 (550)	353 (600)	518 (880)	730 (1,240)
Low	294 (500)	324 (550)	483 (820)	648 (1,100)
Quiet	265 (450)	283 (480)	442 (750)	607 (1,030)
Noise Level dB(A) (Clg/Htg): Hi	28/28	29/29	32/33	33/35
Medium	27/26	28/28	31/32	32/34
Low	26/25	27/27	30/31	30/32
Quiet	25/24	26/24	29/29	29/29
Running Current Rated (A): Cooling	0.30	0.35	0.44	0.66
Heating	0.30	0.35	0.44	0.66
Power Use Rated (W): Cooling	49	58	73	111
Heating	49	58	73	111
Fan Speeds Stage	4 + Auto	4 + Auto	4 + Auto	4 + Auto
Air Filter	Washable	Washable	Washable	Washable
Connection Method	Flare	Flare	Flare	Flare
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4	suc 5/8 dis 1/4
Net Weight lbs. (kg)	41 (19)	41 (19)	50 (23)	59 (27)
Dimensions: Height Inch (mm)	7-25/32 (198)	7-25/32 (198)	7-25/32 (198)	7-25/32 (198)
Width Inch (mm)	27-9/16 (700)	27-9/16 (700)	35-7/16 (900)	43-5/16 (1,100)
Depth Inch (mm)	24-13/32 (620)	24-13/32 (620)	24-13/32 (620)	24-13/32 (620)
Supply Duct Flange	5-15/16 (151)	5-15/16 (151)	5-15/16 (151)	5-15/16 (151)
Dimensions: Height Inch (mm)	25-19/32 (650)	25-19/32 (650)	33-15/32 (850)	41-11/32 (1,050)
Width Inch (mm)	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)
Depth Inch (mm)	3/4 (19)	3/4 (19)	3/4 (19)	3/4 (19)
Return Duct Flange	6-27/32 (174)	6-27/32 (174)	6-27/32 (174)	6-27/32 (174)
Dimensions: Height Inch (mm)	22-19/32 (574)	22-19/32 (574)	30-15/32 (774)	38-11/32 (974)
Width Inch (mm)	3/4 (19) (Flat)	3/4 (19) (Flat)	3/4 (19) (Flat)	3/4 (19) (Flat)
Depth Inch (mm)	3/4 (19) (Flat)	3/4 (19) (Flat)	3/4 (19) (Flat)	3/4 (19) (Flat)
Refrigerant	R410A	R410A	R410A	R410A

Field Supplied Filters

Filters are sized to keep velocities and static pressure loss low. This will insure sufficient static pressure is available for ductwork, fittings and supply and return grilles. Alternative filter sizes with equivalent face areas can be used.

	ARU 9RLF	ARU 12RLF	ARU 18RLF	ARU 24RLF
CFM	353	353	547	806
Typical Filter Size	12 x 20	12 x 20	14 x 25	18 x 30
Velocity, FPM	212	212	225	215
Unit External SP, in. W.C.	0.36	0.36	0.36	0.20
1" Fiberglass Filter				
SP Loss, in. W.C.	0.04	0.04	0.04	0.04
Available Static Pressure	0.32	0.32	0.32	0.16
1" MERV 8 Pleated Filter				
SP Loss, in. W.C.	0.12	0.12	0.14	0.13
Available Static Pressure	0.24	0.24	0.22	0.07
2" MERV 8 Pleated Filter				
SP Loss, in. W.C.	0.07	0.07	0.08	0.07
Available Static Pressure	0.29	0.29	0.28	0.13

Compact Cassettes 9, 12, and 18,000 BTUs




AUU9RLF, AUU12RLF, AUU18RLF



Easy Installation


Fits into a standard ceiling tile*.



*Dimensions of outer grille are 27-9/16" x 27-9/16" and may overlap adjacent tiles.

2-Stage Turbo Fan

Air distribution is evenly spread across the heat exchanger by the new 2 stage turbo fan which produces two separate airflow streams.



Standard Features

- Wired Remote Control
- Sleep Timer
- Dry Mode
- Auto Louver: Up/ Down
- Quiet Mode
- Auto Restart/Reset
- Remote Temperature Sensor
- High Ceiling Mode
- Condensate Pump
- 2-Stage Turbo Fan
- Minimum Heat Mode+
- Fresh Air Intake**



	AUU9RLF Heat Pump	AUU12RLF Heat Pump	AUU18RLF Heat Pump
Nominal Cooling BTU/h	9,000	12,000	18,000
Nominal Heating BTU/h	10,200	13,500	20,000
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1	208-230/60/1
Air Circ. C.F.M. (m ³ /h): Hi	318 (540) Clg or Htg	359 (610) Clg or Htg	441 (750) Clg 471 (800) Htg
Medium	288 (490) Clg or Htg	312 (530) Clg or Htg	359 (610) Clg 418 (710) Htg
Low	259 (440) Clg or Htg	277 (470) Clg or Htg	306 (520) Clg 353 (600) Htg
Quiet	230 (390) Clg or Htg	241 (410) Clg or Htg	241 (410) Clg 265 (450) Htg
Noise Level dB(A) Clg/Htg: Hi	33/34	37/37	42/44
Medium	31/32	33/33	37/40
Low	29/29	31/31	33/37
Quiet	27/27	28/28	29/30
Running Current Rated (A): Cooling	0.15	0.19	0.30
Heating	0.15	0.19	0.30
Power Use Rated/Max (W): Clg	18	23	39
Heating	18	23	39
Fan Speeds Stage	4+auto	4+auto	4+auto
Air Direction: Vertical	Automatic	Automatic	Automatic
Air Filter	Washable	Washable	Washable
Front Grille	UTG-CCGF*	UTG-CCGF*	UTG-CCGF*
Connection Method	Flare	Flare	Flare
Conn. Pipe Diameter Inch	suc 3/8 dis 1/4	suc 3/8 dis 1/4	suc 1/2 dis 1/4
Net Weight lbs. (kg)	33 (15)	33 (15)	33 (15)
Chassis Dim: Height Inch (mm)	9-11/16 (245)	9-11/16 (245)	9-11/16 (245)
Width Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Depth Inch (mm)	22-7/16 (570)	22-7/16 (570)	22-7/16 (570)
Grille Dim: Height Inch (mm)	1-15/16 (49)	1-15/16 (49)	1-15/16 (49)
Width Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Depth Inch (mm)	27-9/16 (700)	27-9/16 (700)	27-9/16 (700)
Refrigerant	R410A	R410A	R410A

+ Available only with optional wireless remote control.

**Requires Fujitsu's Optional Fresh Air Kit part #UTZ-VXAA. Allows for a 4-inch flex duct connection. Requires a field supplied duct booster fan capable of 60 CFM at .2"W.C. or 90 CFM at .4"W.C. For fan static pressure requirements, see installation manual. Add hood, filter and duct losses for fan total static pressure requirements. Will add 4" to the height of the indoor unit.

* Compact Cassette Grille UTG-CCGF sold separately. Must order one with each compact cassette.

Fresh Air Kit** UTZ-VXAA

Mixes room air then passes through the heat exchanger.




Multi Zone Outdoor Units 18, 24 and 36,000 BTUs

**AOU18RLXFZ, AOU24RLXFZ,
AOU36RLXFZ**



Compact Size

The compact size of the outdoor units allows for many installation opportunities.



DC Twin Rotary Compressor

A high performance, low noise, large capacity DC twin rotary compressor is used.



Nominal Capacities, SEER and HSPF Ratings

Data below is based on AHRI 210/240 non-ducted wall mounted models.

Connectable Indoor Unit *Number*
 Connectable Unit Capacity Class *BTU/h*
 Rated Capacity Cooling/Heating *BTU/h*
 Clg. Operating Range °F(°C)
 Htg. Operating Range °F(°C)
 Input Power: Clg/Htg Rated *kW**
 Voltage/Frequency/Phase
 Current: Total Max. (A)
 Minimum Circuit Ampacity (A)
 Recommended Fuse Size (A)
 Outdoor Fan Airflow *CFM (Clg/Htg)*
 Fan: Type x Quantity
 Sound Pressure Level Cooling *dB(A)*
 Sound Pressure Level Heating *dB(A)*
 Pre-Charge Length Total *Ft (m)*
 Max. Length Total *Ft (m)*
 Max. Length Each *Ft (m)*
 Min. Length Total *Ft (m)*
 Min. Length Each *Ft (m)*
 Max. Pipe Height Difference Between Outdoor Unit & Farthest Indoor *Ft (m)*
 Max. Pipe Height Difference Between Indoor Units *Ft (m)*
 Connection Method

Conn. Pipe Diameter *Inch*

Net Weight *lbs. (kg)*

Dimensions: Height *Inch*

mm

Width *Inch*

mm

Depth *Inch*

mm

Refrigerant

AOU 18RLXFZ	AOU 24RLXFZ	AOU 36RLXFZ	AOU 36RLXFZ
Heat Pump ASU9+ASU9	Heat Pump ASU9+ASU7+ASU7	Heat Pump ASU9 x 4	18+18 Combo ASU18+ASU18
2	2 to 3	3 to 4	2
14 to 21,000	14 to 27,000	27 to 39,000	36,000
18,000/22,000	22,000/24,000	35,200/36,400	31,600/35,800
14 to 115 (-10 to 46)	14 to 115 (-10 to 46)	32 to 115 (0 to 46)	50 to 115 (10 to 46)
5 to 75 (-15 to 24)	5 to 75 (-15 to 24)	14 to 75 (-10 to 24)	14 to 75 (-10 to 24)
1.44/1.87	1.76/1.73	4.00/3.00	3.98/3.66
208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
10.0	13.7	20.1	20.1
13	17	25	25
25	25	30	30
1,795/1,619	1,942/1,942	2,119/2,237	2,119/2,237
Propeller x 1	Propeller x 1	Propeller x 1	Propeller x 1
49	51	53	53
49	52	55	55
98 (30)	98 (30)	164 (50)	66 (20)
164 (50)	164 (50)	230 (70)	131 (40)
82 (25)	82 (25)	82 (25)	82 (25)
49 (15)	49 (15)	66 (20)	49 (15)
16 (5)	16 (5)	16 (5)	25 (7.5)
49 (15)	49 (15)	49 (15)	49 (15)
33 (10)	33 (10)	33 (10)	33 (10)
Flare	Flare	Flare	Flare
Liq. 1/4 x 2 Suc. 3/8 x 2	Liq. 1/4 x 3 Suc. 1/2 x 1, 3/8 x 2	Liq. 1/4 x 4 Suc. 1/2 x 1, 3/8 x 3	Liq. 3/8 x 2 Suc. 1/2 x 2
119 (54)	124 (56)	149 (68)	149 (68)
27-9/16	27-9/16	32-11/16	32-11/16
700	700	830	830
35-7/16	35-7/16	35-7/16	35-7/16
900	900	900	900
13	13	13	13
330	330	330	330
R410A	R410A	R410A	R410A

118+18 is the only 2 indoor unit (ASU, ARU or AAU) combination and requires K9FZ1818.
 2See table on page 19 for allowed combinations within this connectable capacity range.

Model	Indoor Unit		Cooling Capacity Btu/h	EER	SEER	Heating Capacity Btu/h		COP	HSPF
	Type	Combination				95 F	47 F		
AOU18RLXFZ	Non-Ducted	ASU9+ASU9	18,000	12.50	18.0	22,000	13,900	3.44	9.3
	Ducted	-	18,000	12.10	16.0	22,000	13,900	3.52	9.0
	Mixed	-	18,000	12.30	17.0	22,000	13,900	3.48	9.2
	Specific	ASU7+ASU12 and ASU9+ASU12	18,000	12.50	18.0	22,000	13,900	3.67	9.0
AOU24RLXFZ	Non-Ducted	ASU9+ASU7+ASU7	22,000	12.50	18.0	24,000	14,100	4.04	9.5
	Ducted	-	22,000	10.60	15.5	24,000	14,100	3.42	9.0
	Mixed	-	22,000	11.55	16.8	24,000	14,100	3.74	9.3
AOU36RLXFZ	Non-Ducted	-	35,200	8.80	16.0	36,400	22,000	3.56	9.4
	Ducted	-	33,800	8.10	14.5	36,400	21,200	3.08	8.7
	Mixed	-	34,400	8.45	15.3	36,400	21,600	3.32	9.1

Yellow rows represent models that are ENERGY STAR® Qualified.

Flex Zone Outdoor Unit 48,000 BTUs

AOU48RLXFZ1



- Connect 2 to 8 indoor units
- 80 to 130% connectable capacity
- Connect 39,000 to 62,000 BTU

2 Indoor Units


18k BTU/h + 24 k BTU/h = 42k BTU/h ..OK
12k BTU/h + 24 k BTU/h = 36k BTU/h ..Not Allowed (below 80%)

8 Indoor Units

7k BTU/h × 8 units = 56k BTU ..OK
9k BTU/h × 8 units = 72k BTU ..Not Allowed (over 130%)

Compact Size

The compact size of outdoor unit AOU48RLXFZ1 allows for many installation opportunities.




Self Diagnostic Feature

This printed circuit board provides three modes of diagnostics - setting, monitoring and function mode, as well as error codes. It also provides a pre-commissioning check function. Setting mode allows optional functions to be selected. Monitoring mode provides temperature for each thermistor, compressor operation and other functions. Function mode provides cooling test run, heating test run and pump down operation.



Piping Flexibility

Contractors can choose the best direction for piping from the outdoor unit.



DC Twin Rotary Compressor

A high performance, low noise, large capacity DC twin rotary compressor is used. Includes Quiet Mode for night operation.



AOU48RLXFZ1 Heat Pump

Connectable Indoor Unit <i>Number</i>	2 to 8
Connectable Indoor Unit <i>Capacity</i>	80 to 130% Nominal (39,000 - 62,000 BTU)
Connectable Branch Box <i>Number</i>	1 to 3
Nominal Cooling <i>BTU/h</i>	48,000
Max Cooling <i>BTU/h</i>	51,100
Nominal Heating <i>BTU/h</i>	54,000
Low Temp. Heating 17°F <i>BTU/h</i>	40,000
Max Heating <i>BTU/h</i>	57,000
Clg. Operating Range °F(°C)	23-115 (-5-46)
Htg. Operating Range °F(°C)	5-75 (-15-24)
Input Power: Cooling Rated <i>kW*</i>	5.52 / 5.19 / 5.35
Input Power: Heating Rated <i>kW*</i>	5.02 / 4.89 / 4.96
Voltage/Frequency/Phase	208-230/60/1
Current: Clg Outdoor Max. (A)	24.5 / 23.0 / 23.7
Current: Htg Outdoor Max. (A)	22.3 / 21.7 / 22.0
Recommended Fuse Size (A)	40
Outdoor Fan Speed <i>RPM (Clg/Htg)</i>	890/910
Fan: Type x Quantity	Propeller x 1
Fan Motor Output <i>W</i>	111
Sound Pressure Level Cooling <i>dB(A)</i>	56
Sound Pressure Level Heating <i>dB(A)</i>	58
Max. Pipe Length Total <i>Ft (m)</i>	377 (115)
Max. Pipe Length Between Box & Farthest Indoor Unit <i>Ft (m)</i>	49 (15)
Max. Pipe Height Difference Between Outdoor Unit & Branch Box <i>Ft (m)</i>	98 (30)
Max. Pipe Height Difference Between Indoor Units <i>Ft (m)</i>	49 (15)
Max. Pipe Height Difference Between Outdoor Unit & Farthest Indoor Unit <i>Ft (m)</i>	98 (30)
Connection Method	Flare
Conn. Pipe Diameter <i>Inch</i>	3/8 (Liq.) 5/8 (Suc.)
Net Weight <i>lbs. (kg)</i>	216 (98)
Dimensions: Height <i>Inch</i>	36
<i>mm</i>	914
Width <i>Inch</i>	38-1/4
<i>mm</i>	970
Depth <i>Inch</i>	14-5/8
<i>mm</i>	370
Refrigerant	R410A

*Ducted / Non-Ducted / Mixed

	SEER	HSPF	EER**
Ducted	14.7	9.3	8.7
Non-Ducted	17.0	9.8	9.25
Mixed	15.8	9.5	8.97

**Cooling

Branch Boxes

UTP-PU03A, UTP-PU03B



	UTP-PU03A Primary	UTP-PU03B Secondary
Connectable Indoor Unit	1 ~ 3	1 ~ 3
Max. Combination BTU/h	62,000 Nom.*	62,000 Nom.*
Min. Combination BTU/h	7,000 Nom.*	7,000 Nom.*
Clg. Operating Range °F(°C)	25-115 (-5-46)	25-115 (-5-46)
Htg. Operating Range °F(°C)	5-75 (-15-24)	5-75 (-15-24)
%RH	80 or less	80 or less
Voltage/Frequency/Phase	208-230/60/1	208-230/60/1
Maximum Current Ampacity (A)	15	15
Running Current <i>Rated</i> (A): Cooling	0.050	0.050
Heating	0.050	0.050
Power Use <i>Rated</i> (W): Cooling	10	10
Heating	10	10


*As long as the total system nominal capacity is between 39,000 and 62,000 BTUs.

Warning: Branch boxes are not weather tight enclosures and cannot be mounted outdoors or in damp environments exceeding 80% relative humidity, unless using the Branch Box Outdoor Enclosure, Part #UTP-PX-A. See Page 39 for more information.

	UTP-PU03A Primary	UTP-PU03B Secondary
Dimensions: Gross (Flare to Flare):		
Height x Width x Depth <i>Inch</i>	7-5/8 x 33 x 14-5/8	7-5/8 x 33 x 14-5/8
Height x Width x Depth <i>mm</i>	195 x 838 x 370	195 x 838 x 370
Dimensions: Net (Metal Box Only):		
Height x Width x Depth <i>Inch</i>	7-5/8 x 17 x 14-5/8	7-5/8 x 17 x 14-5/8
Height x Width x Depth <i>mm</i>	195 x 433 x 370	195 x 433 x 370
Net Weight <i>lbs. (kg)</i>	20 (9)	20 (9)
Conn. Pipe Diameter - Main <i>Inch</i>	(3/8 Liq. x 5/8 Suc.)	(3/8 Liq. x 5/8 Suc.)
Conn. Pipe Diameter - Branch <i>Inch</i>	(1/4 Liq. x 1/2 Suc.)	(1/4 Liq. x 1/2 Suc.)
Connection Method	3 pair Flare	3 pair Flare
Connection Adapter Included <i>Inch</i>	(1/2MF x 3/8FF) x 3 (1/2MF x 5/8FF) x 3 No adapter needed for 18k BTU	(1/2MF x 3/8FF) x 3 (1/2MF x 5/8FF) x 3 No adapter needed for 18k BTU

Allowed Branch Box Mounting Direction

Threaded Rod Mount



By reversing the electrical box position you can orient the inlet and outlet pipes into a left hand or right hand configuration.

Horizontal Wall Mount






By reversing the electrical box position you can orient the inlet and outlet pipes into a left hand or right hand configuration.

Vertical Wall Mount






You cannot reverse the electrical box position when mounting the branch box vertically.

Clearances



Dimensions In (mm)



Branch Box Outdoor Enclosure

UTP-PX-A



The Branch Box Outdoor Enclosure is used to mount the indoor style Branch Box outdoors. The Branch Box Outdoor Enclosure is a painted metal cover to match the condensing unit. When Branch Box Outdoor Enclosure is not required, see Installation Manual for indoor mounting instructions.


Allowed Mounting Positions



Dimensions in. (mm)	
Net (HxWxD)	8-11/16 x 32 x 17-7/8 (220 x 813 x 454)
Gross (HxWxD)	3-15/16 x 33-11/16 x 20-5/16 (100 x 880 x 515)
Weight lbs. (kg)	
Net Branch Box cover only	22 (10)
Net Branch Box + Cover	44.1(20)
Gross	30.9 (14)




Dimensions In (mm)




Separation Tube Assembly Kit


UTP-SX248A



Size	Liquid Inch	3/8 x 3/8 x 3/8
	Suction Inch	5/8 x 5/8 x 5/8




Wiring




Branch Box Terminal Connections

Miswiring Detection


- Errors Detected For...
- Miswired terminals
 - Incorrect indoor unit
 - Less than 2 or more than 8 indoor units
 - Less than 39,000 or more than 62,000 BTUs



Piping



		Liquid pipe	Adaptor	Gas pipe
Branch Box to Indoor	7,000 BTU	1/4 inch	included	3/8 inch
	9,000 BTU		included	
	12,000 BTU		included	
	18,000 BTU		n/a	
	24,000 BTU		included	
Calculate Refrigerant Charge Factory Charge 7.6 lb (3.45 kg) Unit pre-charged to 0 feet	Pipe Diameter	Location		Additional Refrig.
	3/8"	Outdoor to Branch Box		0.624 oz./ft. or 58g/meter
	1/4"	Branch Box to Indoor Unit		0.224 oz./ft. or 21g/meter
$(\text{Total length of } 3/8" \text{ liquid line} \times 0.624 \text{ oz./ft. or } 58\text{g/meter}) + (\text{Total length of } 1/4" \text{ liquid line} \times 0.224 \text{ oz./ft. or } 21\text{g/meter})$ $(a+b+c+d+e) \times 0.624 \text{ oz./ft. or } 58\text{g/meter} + (f+g+h+i+j+k+l+m) \times 0.224 \text{ oz./ft. or } 21\text{g/meter} = \text{additional refrigerant}$				



Allowable Combinations for AOU18RLXFZ, AOU24RLXFZ, AOU36RLXFZ

52 Combinations Based on BTU
Over 597 Combinations Based on Indoor Type and BTU



ASU7RLF, ASU9RLF,
ASU9RLS2, ASU12RLF,
ASU12RLS2, ASU15RLS2,
ASU18RLF, ASU24RLF



ARU9RLF, ARU12RLF,
ARU18RLF, ARU24RLF



AAU9RLF
AAU12RLF
AAU18RLF



AOU18RLXFZ
AOU24RLXFZ
AOU36RLXFZ

BTU Capacity	7,000	9,000	12,000	15,000	18,000	24,000
--------------	-------	-------	--------	--------	--------	--------

Room/Unit Count	AOU18RLXFZ	AOU24RLXFZ	AOU36RLXFZ	AOU48RLXFZ1	AOU36RLXFZ	AOU18RLXFZ	AOU24RLXFZ	AOU36RLXFZ	AOU48RLXFZ1
2 ROOMS	7 7	-	12 12 15	18 24	18*18	7 7	7 7	12 12 15	15 15 24
	7 9	-	7 7 7 7	24 24	7 7 15	7 9	7 7 7 7	7 9 9	15 18 18
	7 12	-	7 7 7 9	7 9 24	7 7 18	7 12	7 7 7 9	7 7 7 12	15 18 24
	9 9	-	7 7 9 12	7 12 24	7 7 24	9 9	7 7 9 12	7 7 7 15	15 24 24
	9 12	-	7 7 12 12	7 15 18	7 7 18 18	9 12	7 7 12 12	7 7 7 15	18 18 18
3 ROOMS	7 7 -	-	7 7 9 9	7 15 18	7 7 18	7 7 -	7 7 9 9	7 7 9 9	7 7 7 18
	7 9 -	-	7 7 9 12	7 18 18	7 7 24	7 9 -	7 7 9 12	7 7 9 12	7 7 7 24
	7 12 -	-	7 7 12 12	7 18 24	7 7 24	7 12 -	7 7 12 12	7 7 9 15	7 7 9 18
	7 15	-	7 7 12 12	7 24 24	7 7 24	7 15	7 7 15	7 7 9 15	7 7 9 24
	7 18	-	7 7 12 12	9 9 24	9 9 24	7 18	7 7 18	7 7 9 15	7 7 9 24
	9 9 -	-	7 7 9 9	9 9 24	9 9 24	9 9 -	9 9 -	7 7 9 15	7 7 9 24
	9 12	-	7 7 9 12	9 12 18	9 9 24	9 12	9 9 12	7 7 9 12	7 7 15 15
	9 15	-	7 7 9 12	9 12 18	9 9 24	9 15	9 9 15	7 7 9 12	7 7 15 15
	9 18	-	7 7 9 12	9 12 18	9 9 24	9 18	9 9 18	7 7 9 12	7 7 15 15
	12 12	-	7 7 9 12	9 12 18	9 9 24	12 12	12 12	7 7 9 12	7 7 15 15
12 15	-	7 7 9 12	9 12 18	9 9 24	12 15	12 15	7 7 9 12	7 7 15 15	
4 ROOMS	7 7 7	-	7 7 12 12	7 15 18	7 7 24	7 7 7	7 7 7 7	7 7 12 12	7 7 15 15
	7 7 9	-	7 7 12 12	7 15 18	7 7 24	7 7 9	7 7 7 9	7 7 12 12	7 7 15 15
	7 7 12	-	7 7 12 12	7 15 18	7 7 24	7 7 12	7 7 7 12	7 7 12 12	7 7 15 15
	7 7 15	-	7 7 12 12	7 15 18	7 7 24	7 7 15	7 7 7 15	7 7 12 12	7 7 15 15
	7 7 18	-	7 7 12 12	7 15 18	7 7 24	7 7 18	7 7 7 18	7 7 12 12	7 7 15 15
	9 9 -	-	7 7 12 12	7 15 18	7 7 24	9 9 -	9 9 -	7 7 12 12	7 7 15 15
	9 12	-	7 7 12 12	7 15 18	7 7 24	9 12	9 9 12	7 7 12 12	7 7 15 15
	9 15	-	7 7 12 12	7 15 18	7 7 24	9 15	9 9 15	7 7 12 12	7 7 15 15
	9 18	-	7 7 12 12	7 15 18	7 7 24	9 18	9 9 18	7 7 12 12	7 7 15 15
	12 12	-	7 7 12 12	7 15 18	7 7 24	12 12	12 12	7 7 12 12	7 7 15 15
	12 15	-	7 7 12 12	7 15 18	7 7 24	12 15	12 15	7 7 12 12	7 7 15 15
	12 18	-	7 7 12 12	7 15 18	7 7 24	12 18	12 18	7 7 12 12	7 7 15 15
	15 15	-	7 7 12 12	7 15 18	7 7 24	15 15	15 15	7 7 12 12	7 7 15 15
	18 18	-	7 7 12 12	7 15 18	7 7 24	18 18	18 18	7 7 12 12	7 7 15 15
	24 24	-	7 7 12 12	7 15 18	7 7 24	24 24	24 24	7 7 12 12	7 7 15 15

*The optional kit "K9FZ1818 (UTP-MU36A2)" is necessary for dual zone system "18+18". **Wall mounted type ASU18RLF can not be connected in this combination. "-" represents available circuit for future expansion when connecting this combination.

Allowable Combinations for AOU48RLXFZ1

259 Combinations Based on BTU

9,131 Combinations Based on Indoor Type and BTU



ASU7RLF, ASU9RLF,
ASU9RLS2, ASU12RLF,
ASU12RLS2, ASU15RLS2,
ASU18RLF, ASU24RLF



ARU9RLF, ARU12RLF,
ARU18RLF, ARU24RLF



AUU9RLF
AAU12RLF
AAU18RLF



AOU48RLXFZ1

■ = Allowed "Connectable Capacity" combinations between 100 and 130%

Indoor Units	BTU Values	Total BTU
4 INDOOR UNITS	15 15 15 18	60
	7 7 7 7 12	40
	7 7 7 7 15	42
	7 7 7 7 18	46
	7 7 7 7 24	52
	7 7 7 9 9	39
	7 7 7 9 12	42
	7 7 7 9 15	44
	7 7 7 9 18	48
	7 7 7 9 24	54
	7 7 7 12 12	45
	7 7 7 12 15	47
	7 7 7 12 18	51
	7 7 7 12 24	57
	7 7 7 15 15	49
	7 7 7 15 18	53
	7 7 7 15 24	59
	7 7 7 18 18	57
	7 7 9 9 9	41
	7 7 9 9 12	44
7 7 9 9 15	46	
7 7 9 9 18	50	
7 7 9 9 24	56	
7 7 9 12 12	47	
7 7 9 12 15	49	
7 7 9 12 18	53	
7 7 9 12 24	59	
7 7 9 15 15	51	
7 7 9 15 18	55	
7 7 9 15 24	61	
7 7 9 18 18	59	
7 7 12 12 12	50	
7 7 12 12 15	52	
7 7 12 12 18	56	
7 7 12 12 24	62	
7 7 12 15 15	54	
7 7 12 15 18	58	
7 7 12 15 24	62	
7 7 15 15 15	60	
7 7 15 15 18	62	
7 7 15 15 24	66	
7 9 9 9 9	43	
5 INDOOR UNITS	7 9 9 9 12	46
	7 9 9 9 15	48
	7 9 9 9 18	52
	7 9 9 9 24	58
	7 9 9 12 12	49
	7 9 9 12 15	51
	7 9 9 12 18	55
	7 9 9 12 24	61
	7 9 9 15 15	53
	7 9 9 15 18	57
	7 9 9 15 24	63
	7 9 9 18 18	61
	7 9 12 12 12	52
	7 9 12 12 15	54
	7 9 12 12 18	58
	7 9 12 12 24	64
	7 9 12 15 15	56
	7 9 12 15 18	60
	7 9 12 15 24	66
	7 9 15 15 15	58
7 9 15 15 18	62	
7 12 12 12 12	55	
7 12 12 12 15	57	
7 12 12 12 18	61	
7 12 12 12 24	67	
7 12 12 15 15	59	
7 12 15 15 15	61	
9 9 9 9 9	45	
9 9 9 9 12	48	
9 9 9 9 15	50	
9 9 9 9 18	54	
9 9 9 9 24	60	
9 9 9 12 12	51	
9 9 9 12 15	53	
9 9 9 12 18	57	
9 9 9 12 24	63	
9 9 9 15 15	55	
9 9 9 15 18	59	
9 9 9 15 24	65	
9 9 12 12 12	54	
9 9 12 12 15	56	
9 9 12 12 18	60	
9 9 12 12 24	66	
9 9 12 15 15	58	
9 9 12 15 18	62	
9 9 12 15 24	68	
9 9 15 15 15	60	
9 12 12 12 12	57	
9 12 12 12 15	59	
9 12 12 12 18	63	
9 12 12 12 24	69	
9 12 12 15 15	61	
12 12 12 12 12	60	
12 12 12 12 15	62	
7 7 7 7 7 7 7	42	
7 7 7 7 7 7 9	44	
7 7 7 7 7 7 12	47	
7 7 7 7 7 7 15	49	
7 7 7 7 7 7 18	53	
7 7 7 7 7 7 24	59	
7 7 7 7 9 9 9	46	
7 7 7 7 9 9 12	49	
7 7 7 7 9 9 15	51	
7 7 7 7 9 9 18	55	
7 7 7 7 9 9 24	61	
7 7 7 7 12 12 12	52	
7 7 7 7 12 12 15	54	
7 7 7 7 12 12 18	58	
7 7 7 7 12 12 24	64	
7 7 7 7 15 15 15	56	
7 7 7 7 15 15 18	60	
7 7 7 7 15 15 24	66	
7 7 7 7 18 18 18	62	
7 7 7 9 9 9 9	48	
7 7 7 9 9 9 12	51	
7 7 7 9 9 9 15	53	
7 7 7 9 9 9 18	57	
7 7 7 9 9 12 12	54	
7 7 7 9 9 12 15	56	
7 7 7 9 9 12 18	60	
7 7 7 9 9 12 24	66	
7 7 7 9 9 15 15	58	
7 7 7 9 9 15 18	62	
7 7 7 9 9 15 24	68	
7 7 7 9 12 12 12	57	
7 7 7 9 12 12 15	59	
7 7 7 9 12 12 18	63	
7 7 7 9 12 12 24	69	
7 7 7 9 12 15 15	61	
7 7 7 9 12 15 18	65	
7 7 7 9 12 15 24	71	
7 7 9 9 9 9 9	50	
7 7 9 9 9 9 12	53	
7 7 9 9 9 9 15	55	
7 7 9 9 9 9 18	59	
7 7 9 9 9 12 12	56	
7 7 9 9 9 12 15	58	
7 7 9 9 9 12 18	62	
7 7 9 9 9 12 24	68	
7 7 9 9 9 15 15	60	
7 7 9 9 9 15 18	64	
7 7 9 9 9 15 24	70	
7 7 9 9 12 12 12	57	
7 7 9 9 12 12 15	59	
7 7 9 9 12 12 18	63	
7 7 9 9 12 12 24	69	
7 7 9 9 12 15 15	61	
7 7 9 9 12 15 18	65	
7 7 9 9 12 15 24	71	
7 7 9 9 15 15 15	62	
7 7 9 9 15 15 18	66	
7 7 9 9 15 15 24	72	
7 7 9 12 12 12 12	60	
7 7 9 12 12 12 15	62	
7 7 9 12 12 12 18	66	
7 7 9 12 12 12 24	72	
7 7 9 12 12 15 15	64	
7 7 9 12 12 15 18	68	
7 7 9 12 12 15 24	74	
7 7 9 12 15 15 15	66	
7 7 9 12 15 15 18	70	
7 7 9 12 15 15 24	76	
7 7 9 15 15 15 15	68	
7 7 9 15 15 15 18	72	
7 7 9 15 15 15 24	78	
7 9 9 9 9 9 9 9	61	
7 9 9 9 9 9 9 12	64	
7 9 9 9 9 9 9 15	66	
7 9 9 9 9 9 9 18	70	
7 9 9 9 9 9 12 12	62	
7 9 9 9 9 9 12 15	64	
7 9 9 9 9 9 12 18	68	
7 9 9 9 9 9 12 24	74	
7 9 9 9 9 9 15 15	66	
7 9 9 9 9 9 15 18	70	
7 9 9 9 9 9 15 24	76	
7 9 9 9 9 12 12 12	63	
7 9 9 9 9 12 12 15	65	
7 9 9 9 9 12 12 18	69	
7 9 9 9 9 12 12 24	75	
7 9 9 9 9 12 15 15	65	
7 9 9 9 9 12 15 18	69	
7 9 9 9 9 12 15 24	75	
7 9 9 9 9 15 15 15	67	
7 9 9 9 9 15 15 18	71	
7 9 9 9 9 15 15 24	77	
7 9 9 9 12 12 12 12	64	
7 9 9 9 12 12 12 15	66	
7 9 9 9 12 12 12 18	70	
7 9 9 9 12 12 12 24	76	
7 9 9 9 12 12 15 15	66	
7 9 9 9 12 12 15 18	70	
7 9 9 9 12 12 15 24	76	
7 9 9 9 12 15 15 15	68	
7 9 9 9 12 15 15 18	72	
7 9 9 9 12 15 15 24	78	
7 9 9 9 15 15 15 15	70	
7 9 9 9 15 15 15 18	74	
7 9 9 9 15 15 15 24	80	
7 9 9 12 12 12 12 12	65	
7 9 9 12 12 12 12 15	67	
7 9 9 12 12 12 12 18	71	
7 9 9 12 12 12 12 24	77	
7 9 9 12 12 12 15 15	67	
7 9 9 12 12 12 15 18	71	
7 9 9 12 12 12 15 24	77	
7 9 9 12 12 15 15 15	69	
7 9 9 12 12 15 15 18	73	
7 9 9 12 12 15 15 24	79	
7 9 9 12 15 15 15 15	71	
7 9 9 12 15 15 15 18	75	
7 9 9 12 15 15 15 24	81	
7 9 9 15 15 15 15 15	73	
7 9 9 15 15 15 15 18	77	
7 9 9 15 15 15 15 24	83	
7 9 9 15 15 15 18 18	75	
7 9 9 15 15 15 18 24	79	
7 9 9 15 15 15 24 24	85	
7 9 9 15 18 18 18 18	77	
7 9 9 15 18 18 18 24	81	
7 9 9 15 18 18 24 24	87	
7 9 9 18 18 18 18 18	79	
7 9 9 18 18 18 18 24	83	
7 9 9 18 18 18 24 24	89	
7 9 9 18 18 24 24 24	95	
7 9 9 24 24 24 24 24	84	
7 9 9 24 24 24 24 24	88	
7 9 9 24 24 24 24 24	94	
7 9 9 24 24 24 24 24	98	
7 9 9 24 24 24 24 24	104	
7 9 9 24 24 24 24 24	108	
7 9 9 24 24 24 24 24	114	
7 9 9 24 24 24 24 24	118	
7 9 9 24 24 24 24 24	124	
7 9 9 24 24 24 24 24	128	
7 9 9 24 24 24 24 24	134	
7 9 9 24 24 24 24 24	138	
7 9 9 24 24 24 24 24	144	
7 9 9 24 24 24 24 24	148	
7 9 9 24 24 24 24 24	154	
7 9 9 24 24 24 24 24	158	
7 9 9 24 24 24 24 24	164	
7 9 9 24 24 24 24 24	168	
7 9 9 24 24 24 24 24	174	
7 9 9 24 24 24 24 24	178	
7 9 9 24 24 24 24 24	184	
7 9 9 24 24 24 24 24	188	
7 9 9 24 24 24 24 24	194	
7 9 9 24 24 24 24 24	198	
7 9 9 24 24 24 24 24	204	
7 9 9 24 24 24 24 24	208	
7 9 9 24 24 24 24 24	214	
7 9 9 24 24 24 24 24	218	
7 9 9 24 24 24 24 24	224	
7 9 9 24 24 24 24 24	228	
7 9 9 24 24 24 24 24	234	
7 9 9 24 24 24 24 24	238	
7 9 9 24 24 24 24 24	244	
7 9 9 24 24 24 24 24	248	
7 9 9 24 24 24 24 24	254	
7 9 9 24 24 24 24 24	258	
7 9 9 24 24 24 24 24	264	
7 9 9 24 24 24 24 24	268	
7 9 9 24 24 24 24 24	274	
7 9 9 24 24 24 24 24	278	
7 9 9 24 24 24 24 24	284	
7 9 9 24 24 24 24 24	288	
7 9 9 24 24 24 24 24	294	
7 9 9 24 24 24 24 24	298	
7 9 9 24 24 24 24 24	304	
7 9 9 24 24 24 24 24	308	
7 9 9 24 24 24 24 24	314	
7 9 9 24 24 24 24 24	318	
7 9 9 24 24 24 24 24	324	
7 9 9 24 24 24 24 24	328	
7 9 9 24 24 24 24 24	334	
7 9 9 24 24 24 24 24	338	
7 9 9 24 24 24 24 24	344	
7 9 9 24 24 24 24 24	348	
7 9 9 24 24 24 24 24	354	
7 9 9 24 24 24 24 24	358	
7 9 9 24 24 24 24 24	364	
7 9 9 24 24 24 24 24	368	
7 9 9 24 24 24 24 24	374	
7 9 9 24 24 24 24 24	378	
7 9 9 24 24 24 24 24	384	
7 9 9 24 24 24 24 24	388	
7 9 9 24 24 24 24 24	394	
7 9 9 24 24 24 24 24	398	
7 9 9 24 24 24 24 24	404	
7 9 9 24 24 24 24 24	408	
7 9 9 24 24 24 24 24	414	
7 9 9 24 24 24 24 24	418	
7 9 9 24 24 24 24 24	424	
7 9 9 24 24 24 24 24	428	
7 9 9 24 24 24 24 24	434	
7 9 9 24 24 24 24 24	438	
7 9 9 24 24 24 24 24	444	
7 9 9 24 24 24 24 24	448	
7 9 9 24 24 24 24 24	454	
7 9 9 24 24 24 24 24	458	
7 9 9 24 24 24 24 24	464	
7 9 9 24 24 24 24 24	468	
7 9 9 24 24 24 24 24	474	
7 9 9 24 24 24 24 24	478	
7 9 9 24 24 24 24 24	484	
7 9 9 24 24 24 24 24	488	
7 9 9 24 24 24 24 24	494	
7 9 9 24 24 24 24 24	498	
7 9 9 24 2		

Wall Mounts

Wired Remote Controller*

UTY-RNBYU*/UTY-RNNUM*



The wired remote controller with its unique lock function and sleek design provides full feature access to property managers, building owners, and facility maintenance, as well as providing basic comfort features to tenants, employees, and teachers.

Wired Remote Controller

UTY-RVNUM



Features a large backlit LCD display and displays the room temperature. Provides full feature access to property managers, building owners, and facility maintenance, as well as providing basic comfort features to tenants, employees, and teachers.

Simple Remote Controller

UTY-RSNUM*



Suitable when only basic operations are required for hotels, offices and other places where there is frequent arrival and departure of occupants. Remote does not allow any timer settings.

Dry Contact Wire Kit*

UTY-XWZX/UTY-XWZXZ5



Turns system on or off using a normally open circuit. For example in home automation, BMS integration of only On/Off operation, occupancy sensor, key card switch, or lead-lag control of other heating/cooling devices.

Interface Kit

UTY-TWBXF**



Required to connect the ASU9RLS2, ASU12RLS2 and ASU15RLS2 to Wired Remote UTY-RNNUM, Dry Contact Wire Kit UTY-XWZXZ5, and Simple Remote Control UTY-RSNUM.

Interface Kit

UTY-XCBXZ1**



Required to connect ASU7RLF, 9RLF, 12RLF and ASU15RLS to Wired Remote UTY-RNNUM, Dry Contact Wire Kit UTY-XWZX, and Simple Remote Control UTY-RSNUM.

Universal Mount/Ceiling Susp. Ceiling Suspended

Wired Remote Controller


UTY-RNBYU**



The wired remote controller with its unique lock function and sleek design provides full feature access to property managers, building owners, and facility maintenance, as well as providing basic comfort features to tenants, employees, and teachers.

Condensate Pump

UTR-DPB24T



OEM design plugs into factory harness for ease of installation. Rated for 11.8" of vertical lift. Only used with System 36RSLX.

Large Cassettes

Fresh Air Intake Kit

KHRS940-25



Kit contains current sensor with built-in relay (Split Core Fixed Threshold Current Status Sensor with Command Relay) and Switching Power Supply. Duct and Fan are field supply. A fan capable of generating 15 CFM at a static pressure of approximately .26 inches W.C. required.

Compact Cassettes

High Humidity Insulation Kit

UTZ-KXGC



Additional insulation for compact cassette units, which may be needed when they are installed in high humidity areas.

Fresh Air Intake Kit

UTZ-VXAA



Mixes room air then passes it through a heat exchanger. Allows for a 4-inch flex duct connection. Requires a field supplied duct booster fan capable of 60 CFM at .2"W.C. or 90 CFM at .4"W.C. For fan static pressure requirements, see installation manual.

Dry Contact Wire Kit

UTY-XWZX



Turns system on or off using a normally open circuit. For example in home automation, BMS integration of only On/Off operation, occupancy sensor, key card switch, or lead-lag control of other heating/cooling devices.

Wireless Remote Controller

UTY-LNHUM



For spaces where there is just no place to mount the wired remote or where wireless operation is preferred.

Simple Remote Controller

UTY-RSNUM



Suitable when only basic operations are required for hotels, offices and other places where there is frequent arrival and departure of occupants. Timer feature is not available.

Air Outlet Shutter Plate

UTR-YDZB



In a 3-way air flow configuration an Air Outlet Shutter Plate kit is required to block air flow of 1 louver.

^ Minimum Heat, Sleep Timer functions will be lost when the wired remote controller is installed.

* Wall mounted ASU7, 9, and 12RLF require accessory interface kit (Part UTY-XCBXZ1) in order to connect this device to them. Wall mounted ASU9, 12, and 15RLS2 require accessory interface kit (Part UTY-TWBXF) in order to connect this device to them.

** Internal thermosensor function in Wired Remote UTY-RNNUM is disabled when using this interface kit.

Things To Know Before You Buy a Fujitsu System

Complete System Warranty

Warranties vary depending on model:

2 Year Parts, 6 Year Compressor Warranty OR

5 Year Parts, 7 Year Compressor Warranty.



Note: Condensing units come pre-charged from factory. Additional refrigerant may be required, be sure to check installation manual for more details.

• Cooling capacity is based on the following conditions:

Indoor temperature: 80°F DB/67°F WB (26.7°C DB/19.4°C WB)

Outdoor temperature: 95°F DB/75°F WB (35°C DB/23.9°C WB)

• Heating capacity is based on the following conditions:

Indoor temperature: 70°F DB (21.1°C DB)

Outdoor temperature: 47°F DB/43°F WB (8.3°C DB/6.1°C WB)

Trademarks

The Fujitsu logo is a registered trademark of Fujitsu Limited. The Halcyon and Halcyon HFI logos and names are trademarks of Fujitsu General America, Inc. ENERGY STAR® is a registered trademark of the EPA and DOE. Copyright © 2013 Fujitsu General America, Inc.

Non-Internet Retail Policy

Internet sales are strictly prohibited and unauthorized. Any HVAC systems purchased on the Internet, from an online retailer or any similar e-tailing website, OR where the original factory serial numbers of the display have been removed, defaced, or replaced in any way WILL NOT BE COVERED BY WARRANTY.

Things To Know Before You Install a Fujitsu System

Warning

Always use a licensed installer or contractor to install this product. Do not try to install the product yourself. Improper installation can result in water or refrigerant leakage, electrical shock, fire or explosion. Use only parts and accessories supplied or specified by Fujitsu. Ask a licensed contractor to install parts and accessories. Use of unauthorized or improper installation of parts and accessories can result in injury or property damage. Read the owner's operation manual carefully before using this product. The owners operation manual provides important safety instructions and warnings which should be followed closely. For any questions or concerns, please contact Fujitsu General America, Inc. Proper sizing and installation of equipment is critical to achieve optimal performance. Split system air conditioners and heat pumps must be matched with appropriate coil components to meet ENERGY STAR criteria. Ask your contractor for details or visit www.energystar.gov.

Heat Pump Disclaimer

In most climates a heat pump will handle all of your heating needs. However, this system sometimes requires some other additional source of heat to satisfy heating requirements in the coldest environments. Almost all of Fujitsu's heat pumps use inverter technology and as such offer a wider operating range and more heat capacity than a standard heat pump but will not provide adequate heating if improperly sized or operated outside of its operating range. Specifications vary by model; please consult your contractor before choosing a heat pump as your only source of heat. Systems will maintain temperature up to +/-4 degrees relative to set temperature. To increase energy efficiency on multi-type systems, you should turn off the evaporators when heating or cooling is not needed.

Disclaimer

Fujitsu's products are subject to continuous improvements. Fujitsu reserves the right to modify product design, specifications and information in this brochure without notice and without incurring any obligations.

Certifications

ISO

ISO14001 is the standard defined by the International Organization for Standardization (ISO) related to environmental management systems. Fujitsu General America, Inc. has been acknowledged by an internationally accredited compliance organization as having an appropriate program of environmental protection procedures and activities to meet the requirements of ISO14001. The air conditioners manufactured by Fujitsu have received ISO9001 series certification for quality assurance.



Intertek



• ISO9001
• ISO14001

ASTM

Our outdoor units shall withstand 1,000 hours of salt spray tested per procedure ASTM B117.

RoHS Compliant

Fujitsu participates in the RoHS Directive, which is the Restriction of Hazardous Substances in electrical and electronic equipment. It is an EU directive intended protect the environment by forcing manufacturers to eliminate or severely curtail the use of cadmium, hexavalent chromium, and lead in all products from automobiles to consumer electronics.



For over 35 years,
making the hottest places cool
and the coolest places...
more comfortable.

Halcyon Mini-Splits Are For You If:

- Central air quotes give you sticker shock
- You don't want to lose closet space to ductwork
- You have warm or cold spots in your home or business
- Your window air conditioner's noise prevents you from hearing the television

Halcyon 



Distributed by:

FUJITSU

Fujitsu General America, Inc.
353 Route 46 West
Fairfield, NJ 07004
Toll Free: (888) 888-3424
Local: (973) 575-0380
Fax: (973) 836-0447
Email: hvac@fujitsugeneral.com
www.fujitsugeneral.com

A subsidiary of
Fujitsu General Limited

Printed in the USA Rev. 3/13
Part #6-26-FG2028

VOC
FREE



AUDI
MEMBER